4K Monitor For Creative Professionals

Digital Cinema 4K 4096 x 2160 ;



31" class (31.0"/787.4mm diagonal)

► 31MU97Z-B

31" class (31.0"/787.4mm diagonal)



Features

1ST 4K MONITOR FOR SMALL MONITOR CATEGORY

31MU97 delivers Digital Cinema 4K with 4096x2160 Full HD and UHD resolution with pivot and height adjustment features for professionals. It makes work environments more convenient than ever and maximizes work productivity in any field of business.

DIGITAL CINEMA 4K

• Digital Cinema 4K (4096x2160) resolution delivers the optimal DCI film industry standard and provides more detailed content at 4096x2160 resolution

IPS DISPLAY WITH ADOBE RGB

• Color differences and color loss are minimized in the wide color gamut and color temperature that covers both the sRGB and CMYK color range.

SINGLE STREAM TRANSPORT

• Supports SST (Single Stream Transport) technology that delivers Digital Cinema 4K resolution from a single source.

DCI-P3 DIGITAL CINEMA COLOR STANDARD

• DCI-P3 Digital Cinema Color Standard reproduces the full dynamic range of shadow, color, saturation and brightness of content accurately.

Specifications

Native Display Resolution 4096 x 2160

High Brightness 320 cd/m²

Contrast Ratio 1,000: 1

5MS (G to G) Response Time,

Built-in Speakers

Tilt, Pivot, Height Adjustable, Base Detachable Stand

Vesa[™] Compliant Wall Mountable

MAC Compatible

3-Year Limited Warranty Parts/Labor/Backlight

VIDEOGRAPHY | GRAPHIC DESIGN | PHOTOGRAPHY



DIGITAL CINEMA 4K (4096x2160) RESOLUTION

The 31MU97 delivers 4K (4096x2160) resolution across a 31" display, providing crisp images with a significant amount of pixels on-screen. 4K (4096x2160) resolution displays over four times the resolution of standard 1920x1080 FHD, and over half a million more pixels than UHD resolution (3840x2160). The most intricate details are displayed perfectly for creative professionals.



SINGLE STREAM TRANSPORT

Supports SST (Single Stream Transport) technology that delivers Digital Cinema 4K resolution from a single source. A smooth viewing experience is achieved while previewing film content without any image sync issues or image tearing like that of other 4K monitors with limited MST (Multi-Stream Transport) or Tiled technology.





IPS DISPLAY WITH ADOBE® RGB OVER 99.5%

By supporting Adobe RGB over 99.5% with IPS technology, the 31MU97minimizes color differences and color loss by using a wide color gamut and color temperature that covers both sRGB and CMYK color ranges. As a result, retouching of photos on the 31MU97 creates final images with vivid and vibrant colors that other VA or LCDs cannot.




DCP-P3 DIGITAL CINEMA COLOR STANDARD

The 31MU97 with DCI-P3 Digital Cinema Color Standard reproduces the full dynamic range of shadow, color, saturation and brightness of content accurately throughout post-production, matching what will be seen in the theater. On-site, superfine editing and over all control can be achieved while using a preview camera.



Full dynamic ranges are accurately reproduced in post-production.





VIDEOGRAPHY | GRAPHIC DESIGN | PHOTOGRAPHY

MAXX AUDIO[®] + 5W Speakers

With two internal 5W speakers and MAXXAUDIO® functions, there is no need for separate high-end monitor speakers. The 31MU97 which supports MAXXAUDIO® delivers high quality sound with a wide range of vibrant, crisp, and clean high and low decibels while reviewing or editing 4K content.

Stereo Speaker



10-BIT COLOR DEPTH (1 billion colors)

10-bit color depth that supports over 1-billion colors is 64 times richer than an 8-bit color display, re-creating colors softly and naturally without color banding. All the images details are displayed with a richer and wider color range that enables accurate, detailed, and natural-looking images. More shades in-between gradient transitions are displayed for a smoother image.



TOTAL COLOR MANAGEMENT

Through detailed color calibration testing, the 31MU97 maintains its color standard with software calibration and a factory preset, minimizing differences in color space and expressions between the original images, monitor screen, and printed result.

*Select the desired color environment through various color tests for color accurate reproduction.





DUAL COLOR SPACE

Simultaneously compare work done using both RGB and sRGB color modes by having half the screen in one mode and the other half in another. View side-by-side, Adobe RGB for print and sRGB for web, to maintain original resolution and any color distortion that may occur in the final project.



FONT SIZE/RESOLUTION CONTROLS

Using the OS system shortcuts, adjusting font sizes, accessing the toolbar, menu fonts or adjusting the resolution is a quick and easy step.

 Mac devices do not support the font adjustment function. When using the font size control, the compatibility with the SW or the level of size adjustments may vary depending on the individual SW.



MULTIPLE COLOR MODES

The 31MU97 comes with variety of color modes ranging from the basic sRGB and Reader, all the way to the more advanced Adobe RGB and DCI-P3 Sim, to accommodate a wide spectrum of needs required by professionals. Simply choose between color mode feature presets or customized calibrations using the joystick.



FLICKER SAFE DISPLAY

Mac

Mac[®] Compatible

LGs Flicker Safe function allows you to spend as long as you want working on or enjoying content without burdening your eyes. This technology reduces the flicker level to almostzero to protect your eyes from exhausting flickers and blue light emissions.





You can connect to various devices with the HDMIx2, MiniDP, Display ports and USB 3.0 ports. And with two Thunderbolt™ports to directly connect a Mac PC or Pegasus2 storage directly to transmit data faster than a USB 3.0. Also, the configured USB Up and three USB 3.0 ports allow you to directly connect a tablet and external HD.





The 31MU97 comes with a 90° pivot function for working on projects that are more vertical than horizontal to keep the size of the project as large as possible on the screen. And easily adjust the height of the screen for optimal working conditions.



Digital Cinema 4K Monitor For Creative Professionals

▶ 31MU97C-B

31" class (31.0"/787.4mm diagonal)

▶ 31MU97Z-B

31" class (31.0"/787.4mm diagonal)

			SPECIAL	Model	31МU97С-В 31МU97Z-В
Dimensions			FEATURES	PC	Yes
				Video	Yes
29.0	0" (736.6mm)	2.1" (53.3mm) 12.5" (154.9mm)(100mm)		DDC/CI	Yes
			7	HDCP PBP	Yes
				PBP Plug & Play	Yes
				Uniformity On/Off	Yes
	(405.4mm) (29.0"			Dual Color Mode	Yes
		(736.6mm) 6.1"			
	6 77		2	Picture Mode	Yes (Custom/sRGB/AdobeRGB/DCM Sim/DCI-P3 Sim/Reader/Calibration1/Calibration
			-	H/W Calibration	Yes
11.8	3" (299.7mm)	9.5" (241.3mm)		Virtual Surround	Yes (MAXX Audio)
ır Jack Panel				Flicker Safe	Yes
MU97C-B				SUPER + Resolution	Yes
				SUPER Energy Saving	Yes
O C				Factory Calibration	Yes
				Others1	True color Pro (S/W)
				Others2	Screen Split with Font/Resolution Control (S/W)
			CABINET	Color	Black Spray
				Stand Color	Titan Silver Spray
				Monitor w/stand	29.0" x 19.0" x 9.5"
				Monitor Weight Monitor w/o stand	21.2 lbs 29.0" x 16.0" x 2.1"
H/P O HDMIIN 1 HD	MIIN 2 mDP-IN DP-IN f			Monitor Weight	17.0 lbs
		5V == 1.1 A AC-IN		Carton Dimensions	38.3" x 20.1" x 6.0"
				Packed Weight	26.5 lbs
NEL N	Aodel	31МU97С-В 31МU97Z-В		Base Detachable	Yes
P	Panel Size	31" class (31.0" diagonal)		Tilt (Angle)	-5°(front)~15°(rear)
P	Panel Type	IPS		Height (mm)	140mm
	Color Gamut (CIE1976)	Adobe RGB over 99.5% / DCI-P3 97%		Pivot	Yes
		Addbe ((db 00e) 99.3767 DCI+F 3 9776		VESA [™] Standard Mount Interface	100mm x 100mm
	Color Depth (Number of Colors)	10bit	POWER	Power Type	Built-in Power
				Power Supply	100~240Vac, 50/60Hz
P	Pixel Pitch (mm)	0.0567mm x 0.1701mm		Normal On (Typ.)	49W (without USB)
A	Aspect Ratio	17:9		Power Save/Sleep Mode (Max)	1.2W (USB3.0)
N	lative Resolution	4096 x 2160		DC Off (Max)	
IN	Brightness			DC OTT (IVIAX)	0.5
		320 cd/m ²	FREQUENCY	HDMI (H-Frequency)	30 ~90kHz
В	2	320 cd/m ²	FREQUENCY		
B	Contrast Ratio (Typ.)	1,000:1	FREQUENCY	HDMI (H-Frequency)	30 -90kHz 56 - 61Hz 30 -134kHz
B	2		FREQUENCY	HDMI (H-Frequency) HDMI (V-Frequency) DisplayPort.(H-Frequency) DisplayPort.(V-Frequency)	30 ~90kHz 56 ~ 61Hz 30 ~134kHz 56 ~ 61Hz
B C D	Contrast Ratio (Typ.)	1,000:1	FREQUENCY	HDMI (H-Frequency) HDMI (V-Frequency) DisplayPort (H-Frequency) DisplayPort (V-Frequency) DisplayPort (PC)	30 -90kHz 56 - 61Hz 30 -134kHz 56 - 61Hz 4096 x 2160 @60
B C D R	Contrast Ratio (Typ.) Dynamic CR (DCR) Response Time	1,000:1 On/Off	RESOLUTION	HDMI (H-Frequency) HDMI (V-Frequency) DisplayPort (H-Frequency) DisplayPort (V-Frequency) DisplayPort (PC) DisplayPort (HDMI)	30 -90kHz 56 - 61Hz 30 -134kHz 56 - 61Hz 4096 x 2160 @60 4096 x 2160 @24
B C D R V	Contrast Ratio (Typ.) Jynamic CR (DCR) Response Time Fiewing Angle	1,000:1 On/Off 5ms (G to G) 178°/178°	RESOLUTION	HDMI (H-Frequency) HDMI (V-Frequency) DsplayPort (H-Frequency) DsplayPort (V-Frequency) DsplayPort (PC) DsplayPort (HDMI) Safety	30 -90kHz 56 - 61Hz 30 -134kHz 56 - 61Hz 4096 x 2160 @60 4096 x 2160 @24 UL(cUL)/CB/TCO 6.0/TU//KC
B C D R V S	iontrast Ratio (Typ.) Jynamic CR (DCR) Response Time Viewing Angle Siurface Treatment	1,000:1 On/Off 5ms (G to G) 178°/178° Advanced Anti-Glare Treatment of the Front Polarizer	RESOLUTION	HDMI (H-Frequency) HDMI (V-Frequency) DisplayPort (H-Frequency) DisplayPort (V-Frequency) DisplayPort (PC) DisplayPort (HDMI)	30 -90kHz 56 - 61Hz 30 -134kHz 56 - 61Hz 4096 x 2160 @60 4096 x 2160 @24
B C D R V S SNAL	iontrast Ratio (Typ.) Jynamic CR (DCR) Response Time Viewing Angle Sturface Treatment IDMI	1,000:1 On/Off 5ms (G to G) 178°/178° Advanced Anti-Glare Treatment of the Front Polarizer Yes (x2, ver 1.4)	RESOLUTION	HDMI (H-Frequency) HDMI (V-Frequency) DsplayPort (H-Frequency) DsplayPort (V-Frequency) DsplayPort (PC) DsplayPort (HDMI) Safety	30 -90kHz 56 - 61Hz 30 -134kHz 56 - 61Hz 4096 x 2160 @60 4096 x 2160 @24 UL(cUL)/CB/TCO 6.0/TU///KC
B C D R V S SNAL	iontrast Ratio (Typ.) Jynamic CR (DCR) Response Time Viewing Angle Siurface Treatment	1,000:1 On/Off 5ms (G to G) 178°/178° Advanced Anti-Glare Treatment of the Front Polarizer	RESOLUTION	HDMI (H-Frequency) HDMI (V-Frequency) DsplayPort (H-Frequency) DsplayPort (V-Frequency) DsplayPort (PC) DsplayPort (HDMI) Safety EMC	30 -90kHz 56 - 61Hz 30 -134kHz 56 - 61Hz 4096 x 2160 @60 4096 x 2160 @24 UL(cUL)/CB/TCO 6.0/TUV/KC FCC-B / CE
GNAL GNAL JPUT) GNAL	iontrast Ratio (Typ.) Jynamic CR (DCR) Response Time Viewing Angle Sturface Treatment IDMI	1,000:1 On/Off 5ms (G to G) 178°/178° Advanced Anti-Glare Treatment of the Front Polarizer Yes (x2, ver 1.4)	RESOLUTION	HDMI (H-Frequency) HDMI (V-Frequency) DsplayPort (H-Frequency) DsplayPort (V-Frequency) DsplayPort (PC) DsplayPort (HDMI) Safety EMC RoHS, REACH	30 -90kHz 56 - 61Hz 30 -134kHz 56 - 61Hz 4096 x 2160 @60 4095 x 2160 @24 UL(cUL)/CB/TCO 6.0/TUV/KC FCC-B / CE Yes Yes Yes (Windows 8)
GNAL GNAL MUT) MUT) GNAL	icontrast Ratio (Typ.) Dynamic CR (DCR) Ieesponse Time fiewing Angle Surface Treatment IDMI DisplayPort	1,000:1 On/Off 5ms (G to G) 178°/178° Advanced Anti-Glare Treatment of the Front Polarizer Yes (x2, ver 1.4) Yes (x1, ver 1.2)	RESOLUTION STANDARD CERTIFICATIONS	HDMI (H-Frequency) HDMI (V-Frequency) DsplayPort (H-Frequency) DsplayPort (V-Frequency) DsplayPort (PC) DsplayPort (HDMI) Safety EMC RoHS, REACH	30 -90kHz 56 - 61Hz 30 -134kHz 56 - 61Hz 4096 x 2160 @60 4096 x 2160 @24 UL(cUL)/CB/TCO 6.0/TUV/KC FCC-B / CE Yes
B C D R V S SNAL PUT) D M T	iontrast Ratio (Typ.) ynamic CR (DCR) lesponse Time fiewing Angle Giurface Treatment HDMI DisplayPort Mini DisplayPort hunderbolt x 2	1,000:1 On/Off 5ms (G to G) 178°/178° Advanced Anti-Glare Treatment of the Front Polarizer Yes (x2, ver 1.4) Yes (x1, ver 1.2) Yes (x1, ver 1.2) No Yes	RESOLUTION STANDARD CERTIFICATIONS WARRANTY UPC	HDMI (H-Frequency) HDMI (V-Frequency) DsplayPort (H-Frequency) DsplayPort (V-Frequency) DsplayPort (PC) DsplayPort (HDMI) Safety EMC RoHS, REACH Windows Power Cord	30 -90kHz 56 - 61Hz 30 -134kHz 56 - 61Hz 4096 x 2160 @60 4096 x 2160 @24 UL(cUL)/CB/TCO 6.0/TUV/KC FCC-B / CE Yes Yes (Windows 8) 3-Year Limited Warranty (Parts/Labor/Backlight)
B C D R V S SNAL IPUT) D M T U U	iontrast Ratio (Typ.) Dynamic CR (DCR) kesponse Time fiewing Angle Surface Treatment HDMI DisplayPort Mini DisplayPort hunderbolt x 2 JSB Up	1,000:1 On/Off Sms (G to G) 178°/178° Advanced Anti-Glare Treatment of the Front Polarizer Yes (x2, ver 1.4) Yes (x1, ver 1.2) No Yes 1(3.0)	RESOLUTION STANDARD CERTIFICATIONS WARRANTY	HDMI (H-Frequency) HDMI (V-Frequency) DsplayPort (H-Frequency) DsplayPort (V-Frequency) DsplayPort (PC) DsplayPort (HDMI) Safety EMC RoHS, REACH Windows Power Cord	30 -90kHz 56 - 61Hz 30 -134kHz 56 - 61Hz 4096 x 2160 @60 4096 x 2160 @24 UL(cLL)/CB/TCO 6.0/TUV/KC FCC-B / CE Yes Yes (Windows 8) 3-Year Limited Warranty (Parts/Labor/Backlight) 7 19192 19763 7 19192 19777 0
B C D R V S SNAL IPUT) D M T U U U U	iontrast Ratio (Typ.) iontrast Ratio (Typ.) ivpannic CR (DCR) Response Time fewing Angle Surface Treatment HDMI DisplayPort fini DisplayPort hunderbolt x 2 ISB Up ISB port	1,000:1 On/Off 5ms (G to G) 178°/178° Advanced Anti-Glare Treatment of the Front Polarizer Yes (x2, ver 1.4) Yes (x1, ver 1.2) Yes (x1, ver 1.2) No Yes	RESOLUTION STANDARD CERTIFICATIONS WARRANTY UPC	HDMI (H-Frequency) HDMI (V-Frequency) DsplayPort (H-Frequency) DsplayPort (V-Frequency) DsplayPort (PC) DsplayPort (HDMI) Safety EMC RoHS, REACH Windows Power Cord DisplayPort to Mini DisplayPort	30 -90kHz 56 - 61Hz 30 -134kHz 56 - 61Hz 4096 x 2160 @60 4096 x 2160 @24 UL(cUL)/CB/TCO 6.0/TUV/KC FCC-B / CE Yes Yes (Windows B) 3-Year Limited Warranty (Parts/Labor/Backlight) 719192 19763 7 19192 19777 0 Yes Yes
GNAL GNAL UPUT) UUT) UU UU UU UU UU	iontrast Ratio (Typ.) Dynamic CR (DCR) kesponse Time fiewing Angle Surface Treatment HDMI DisplayPort Mini DisplayPort hunderbolt x 2 JSB Up	1,000:1 On/Off Sms (G to G) 178°/178° Advanced Anti-Glare Treatment of the Front Polarizer Yes (x2, ver 1.4) Yes (x1, ver 1.2) No Yes 1(3.0)	RESOLUTION STANDARD CERTIFICATIONS WARRANTY UPC	HDMI (H-Frequency) HDMI (V-Frequency) DsplayPort (H-Frequency) DsplayPort (V-Frequency) DsplayPort (PC) DsplayPort (HDMI) Safety EMC RoHS, REACH Windows Power Cord DisplayPort to Mini DisplayPort to Mini DisplayPort to Mini	30 -90kHz 56 - 61Hz 30 -134kHz 56 - 61Hz 4096 x 2160 @60 4095 x 2160 @24 UL(cUL)/CB/TCO 6.0/TUV/KC FCC-B / CE Yes Yes (Windows 8) 3-Year Limited Warranty (Parts/Labor/Backlight) 7 19192 19763 3 7 19192 19777 0 Yes Yes Yes
GNAL PUT) JDIO UTPUT) B JDIO UTPUT) F	iontrast Ratio (Typ.) Dynamic CR (DCR) Response Time frewing Angle Gurface Treatment HDMI DisplayPort hunderbolt x 2 JSB Up JSB port Headphone Out	1,000:1 On/Off 5ms (G to G) 178°/178° Advanced Anti-Glare Treatment of the Front Polarizer Yes (x2, ver 1.4) Yes (x1, ver 1.2) Yes (x1, ver 1.2) No Yes 1 (30) 3 (30) Yes	RESOLUTION STANDARD CERTIFICATIONS WARRANTY UPC	HDMI (H-Frequency) HDMI (V-Frequency) DsplayPort (H-Frequency) DsplayPort (V-Frequency) DsplayPort (PC) DsplayPort (HDMI) Safety EMC RoHS, REACH Windows Power Cord DisplayPort to Mini DisplayPort HDMI USB	30 - 90kHz 56 - 61Hz 30 - 134kHz 56 - 61Hz 4096 x 2160 @60 4095 x 2150 @24 UL(cUL)/CB/TCO 6.0/TUV/KC FCC-B / CE Yes Yes (Windows 8) 3-Year Limited Warranty (Parts/Labor/Backlight) 7 19192 19763 3 7 19192 19777 0 Yes Yes Yes Yes Yes Ses (30)
GNAL IPUT) JUIPUT) JUIPUT) JEAKER J	iontrast Ratio (Typ.) iontrast Ratio (Typ.) ivpannic CR (DCR) Response Time fewing Angle Surface Treatment HDMI DisplayPort fini DisplayPort hunderbolt x 2 ISB Up ISB port	1,000:1 On/Off Sms (G to G) 178°/178° Advanced Anti-Glare Treatment of the Front Polarizer Yes (x2, ver 1.4) Yes (x1, ver 1.2) Yes (x1, ver 1.2) No Yes 1 (3.0) 3 (3.0)	RESOLUTION STANDARD CERTIFICATIONS WARRANTY UPC	HDMI (H-Frequency) HDMI (V-Frequency) DsplayPort (H-Frequency) DsplayPort (V-Frequency) DsplayPort (PC) DsplayPort (HDMI) Safety EMC RoHS, REACH Windows Power Cord DisplayPort to Mini DisplayPort to Mini DisplayPort to Mini	30 -90kHz 56 - 61Hz 30 -134kHz 56 - 61Hz 4096 x 2160 @60 4095 x 2160 @24 UL(cUL)/CB/TCO 6.0/TUV/KC FCC-B / CE Yes Yes (Windows 8) 3-Year Limited Warranty (Parts/Labor/Backlight) 7 19192 19763 3 7 19192 19777 0 Yes Yes Yes



on2)

All screen images are simulated. Dimensions and weights are approximate. Design, specifications, and features subject to change without notice.

 $\ensuremath{\mathbb C}$ Copyright 2015 LG Electronics USA, Inc. All Rights Reserved. "LG Life's Good" is a registered trademark of LG Corp.

ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. In Plane Switching is a trademark of LG Philips LCD Ltd. VESA is a trademark of Video Electronics Standards Association. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

All other product and brand names are trademarks or registered trademarks of their respective companies.



Customer Service: 888.865.3026 www.LGsolutions.com/support

Contact your LG Regional Sales Representative: Channel: 800.897.8871 Hospitality: 800.228.1236 E-mail: info@LGsolutions.com

LG_SPEC_31MU97C-B_31MU97Z_051523_PR



