

27UD69

UD69 SERIES

KEY FEATURES

- 4K UHD (3840 x 2160)
- AMD FreeSync™ with Black Stabiliser
- 5ms GTG Response Time
- sRGB 99% Colour Gamut



PRODUCT FEATURES

PANEL

Screen Size	27" (68cm)
Panel Technology	IPS
Aspect Ratio	16:9
Native	3840 x 2160
Brightness	300cd/m ²
Contrast Ratio	1300:1
Response Time	5ms (GTG)
Viewing Angle (H x V)	178° x 178°
Colour Depth	10bit (8bit + A-FRC)
Color Gamut	sRGB 99%
Surface Treatment	Anti glare ,3H

CONNECTIVITY

Input (Rear)	
Digital	HDMI x 2 (ver2.0) Display Port x 1(ver1.2)
Analogue	
Output (Rear)	
Audio	Headphone Out

ENVIRONMENT CONDITIONS

Operation Temperature	0°C - 40 °C
Operation Humidity	Less than 80 %

ACCESSORIES

Power Cable, HDMI, DP

WARRANTY

3 Years (Parts & Labour)

PHYSICAL SPECIFICATIONS

With stand (WxDxH)	615mm x 455mm x 209mm
Without stand (WxDxH)	615mm x 365mm x 49mm
With stand Weight (kg)	5 kg
Without stand Weight (kg)	4.6 kg
Carton (WxHxD)	694mm x 440mm x 161mm
Packed Weight (kg)	6.9 kg
VESA™ Standard Mount Interface	100 x 100

STANDARD (CERTIFICATION)

Comparative Energy Consumption	115 kWh / year
Star Rating	4 ½ (Stars)
Active Standby	0.2W
Safety	CB Scheme, RCM
ErP/US EPA	Yes / Yes 7.0
EMC	RCM, Class (B)

SPECIAL FEATURES

Reader Mode, Black Stabiliser, Crosshair, DAS Mode

Six Axis Control, Super Resolution+, 4 screen split, FreeSync™,

Stand Tilt -2° (Front) ~ 15° (Rear)

POWER

Power Supply	100 ~ 240V, (50/60Hz)
Power Consumption	29.8W (EPA), 40W (typ)
Typical / Smart Energy Saving on	0.5W
Power Off	0.3W
Power Type	AC Adapter (40W)



*LED LCD Monitors combine LCD screen with LED back light technology

Disclaimer: All product specifications correct at time of printing. Specifications may change without prior notice.