



2020 LG THERMA V  
PRODUCT CATALOGUE

# LG THERMA V PRODUCT CATALOGUE

2020



Distributed by

**LG Electronics**  
[www.lg.com](http://www.lg.com) <http://partner.lg.com>

Copyright © 2020 LG Electronics. All rights reserved.

# INDEX



## INTRODUCTION

LG AS A TRUSTED PARTNER	004
HEAT PUMP TECHNOLOGY	006
THERMA V INTRODUCTION	008
WHAT IS LG THERMA V	010
LG AIR TO WATER HEAT PUMP SOLUTION OVERVIEW	012
THERMA V LINE UP OVERVIEW	014
THERMA V LINE UP INTRODUCTION	016

## THERMA V FEATURES

EXCELLENT PERFORMANCE & EFFICIENCY	022
USER CONVENIENCE	028
EASY INSTALLATION & MAINTENANCE	036

## THERMA V PRODUCTS

<b>MONOBLOC</b>	
R32 MONOBLOC	040
R32 SILENT MONOBLOC	054
<b>SPLIT – WALL HUNG</b>	
R32 SPLIT HYDRO BOX	064
R410A SPLIT HYDRO BOX	072
<b>SPLIT – IWT (INTEGRATED WATER TANK)</b>	
R410A SPLIT IWT	082
<b>SPLIT – FLOOR STANDING</b>	
R410A-R134a SPLIT HIGH TEMPERATURE	092

## THERMA V ACCESSORIES

ACCESSORIES	104
-------------	-----






# LG AS A TRUSTED PARTNER

## Europe Business Infrastructure

Most of LG's heat pump products are manufactured in Korea to ensure high quality production. The highest quality LG provides will be enough to satisfy your customers. In addition, 16 sales offices and 20 academies in Europe are committed to assuring a solid support for your business success. Our highly competitive products produced in Korea are delivered through the European distribution center, ensuring a stable supply of products.

Through our energy lab in Europe, LG is developing heat pump technology that is optimized for European climate and weather, along with continuous product performance verification.



-  Europe B2B regional head office
-  National sales office
-  LG academy
-  European distribution center
-  Europe energy lab



- LG AS A TRUST PARTNER
- HEAT PUMP TECHNOLOGY
- THERMA V INTRODUCTION
- WHAT IS THERMA V
- LG AIR TO WATER HEAT PUMP SOLUTION OVERVIEW
- THERMA V LINE UP OVERVIEW
- THERMA V LINE UP INTRODUCTION


## Engineering Tools

LG provides a variety of software to support THERMA V for all customers including designer, installer, even end user.

### 1. LG THERMA V SELECTOR

LG THERMA V Selector is a mobile application for designer/installer as well as end users providing various simulation. In quick energy simulation, it shows the energy consumption, energy cost and CO<sub>2</sub> emission values that can be reduced compared to conventional heating systems using the minimum input values. In Model selection & energy simulation, quick and accurate model selection is possible using detailed input values such as desired system configuration, required heating and DHW load and it is possible to calculate the payback, faster energy simulation, cost comparison. In addition, through sound simulation, it is possible to easily calculate the sound level value generated according to the installed distance.

\* LG THERMA V Selector is available from Google App store.



### 2. LATS THERMA V

LATS THERMA V is a PC based model selection program of LG THERMA V products, enabling an accurate and quick selection on the best model suitable to each house. In addition to model selection, faster energy simulation and cost comparison to other system is possible. Furthermore, customer is easily able to simulate payback comparing conventional system such as gas boiler, electric boiler by using LATS THERMA V.



### 3. LGMV

LGMV (Monitoring View) is a useful engineering tool that is able to monitor real-time refrigerant cycle of THERMA V. It helps installers to perform effectively start-up and commissioning after THERMA V installation. Also LGMV helps service engineers to figure out the causes of errors and solve the problem faster.



# HEAT PUMP TECHNOLOGY

LG is a true leader of heat pump technology.

As a leading HVAC supplier, LG's heating product portfolio comprises a wide range of highly energy efficient renewable energy systems, Providing the right heating solution for any requirement and building.

## What is Heat Pump System?


### Modernized Technology : Replacing Conventional Boiler

For a long time, conventional heating systems have been used gas, oil, or electric heaters. In such conventional heating systems, environmental aspects such as fossil fuel use and environmental pollution have been overlooked. In recent years, interest in these environmentally friendly devices has been increasing and in order to meet these market demands, LG has further developed their heat pump technology to produce the most efficient, environmentally friendly products in the industry.




### Renewable Technology : Utilizing Renewable Energy

The heat pump is a device that transforms energy from the air, ground and water to useful heat. This transformation is done via the refrigerant cycle. In other words, it refers to a technique for pumping heat from renewable energy resources such as air or water. The energy required to produce the necessary heat compared to boilers using conventional fossil fuels such as gas and oil is one in every four quarters and the remaining three quarters are utilized in renewable energy such as water and air.



- LG AS A TRUST PARTNER
- HEAT PUMP TECHNOLOGY
- THERMA V INTRODUCTION
- WHAT IS THERMA V
- LG AIR TO WATER HEAT PUMP SOLUTION OVERVIEW
- THERMA V LINE UP OVERVIEW
- THERMA V LINE UP INTRODUCTION

### How do Air to Water Heat Pumps Work?



#### ① Outside Air

Heat is extracted from the outside air.

#### ② Evaporator

As low temperature liquid refrigerant absorbs the heat energy from air side, it changes from liquid to vapor phase.

#### ③ Compressor

The vaporized refrigerant flow into compressor. The electric energy to operate the compressor is converted to heat and added to the refrigerant.

#### ④ Condenser

High temperature refrigerant gas flows into the heat exchanger and convey heat energy to water by heat exchange between refrigerant and water.

#### ⑤ Expansion Valve

High pressure liquid refrigerant flow through the expansion valve to restore the refrigerant to original condition.

## The Green Choice for Smart Customers :

### THERMA V™

Expecting Ultimate Heating Energy Efficiency,  
Performance and User Convenience

If you think yourself as smart consumer, you might have faced with some struggles on which AWHP system you should have to choose. The key when choosing would utterly be if it performs well and easily controllable while meeting the strengthened environmental regulations. And considering environmental regulations have been tightened year after year, it's anything but easy for smart consumers – especially for those who are living in Europe – to keep up with the strengthened F-Gas regulations which newly apply across the Europe region since January 1, 2015.

For those who are seeking to meet this tightened regulations, refrigerant R32 takes center stage for the new smart solution as it has much less global warming potential (GWP) than the current refrigerant, R410A. And to live up to smart consumers' needs that energy efficiency comes along with high performance, LG can give smart consumers the crystal clear solution with the THERMA V R32 Products that fulfills the high standard of regulations while bringing additional benefits through increased levels of efficiency and performance.



- Ultimate Energy Efficiency : A+++ in the ErP energy labelling regulation, wide operation range, reduced noise level
- Excellent Performance : R1 Compressor embedded, high heating capacity at low ambient temperature
- User Convenience : LG ThinQ Wi-Fi control, convenient scheduler, wider connectivity, energy monitoring


# WHAT IS LG THERMA V?

## LG'S Advanced Heating Technology


THERMA V is LG's air to water heat pump system, especially designed for the modernized houses (New and renovated houses). THERMA V can be used as a multi-purpose solution for space heating, cooling and hot water. Even more remarkable thing is LG's advanced heating technology, market leading technology that can minimize energy consumption than any solution in the market.



**THERMA V™**



## High Efficiency and Low CO<sub>2</sub> Emission



## Benefits of LG THERMA V




### For House Owner

- Energy saving by utilizing renewable energy and high efficient equipment
- Multiple solution providing space heating and cooling, DHW supply
- Reusability existing heating installation with radiator, boiler, etc
- Economic support by incentive program
- Lower investment cost
- Energy monitoring and remote control



### For Installer & Designer

- Time saving by quick & easy installation and commissioning
- Excellent heating performance even at low ambient temperature
- Less man power for carrying (2 people)
- Low repair cost and less breakdowns with durable parts
- Same controller interface for all LG products. (Need to less training)









### For End-User







































- Multiple solution providing space heating and cooling, DHW supply
- Energy saving by utilizing renewable energy and high efficient equipment
- Simple to use especially for senior people
- Higher comfort by user-friendly controller
- Higher reliability by durable parts and less breakdowns
- Reduce the noise level with low noise mode operation
- Confidence for the green and sustainable solution (High efficiency)

# LG AIR TO WATER HEAT PUMP SOLUTION OVERVIEW

		Monobloc		Split		Split			
		-	Silent	Wall Hung		Floor Standing	IWT		
Line-up		<b>R32 Monobloc</b>	<b>R32 Silent Monobloc</b>	<b>R32 Split</b>	<b>R410A Split</b>	<b>R410A-R134a Split High Temperature</b>	<b>R410A Split IWT</b>		
		1Ø: 5/7/9/12/14/16kW 3Ø: 12/14/16kW	1Ø: 9kW	1Ø: 5/7/9kW	1Ø: 12/14/16kW 3Ø: 12/14/16kW	1Ø: 16kW	1Ø: 9/12/14/16kW 3Ø: 12/14/16kW		
Application		Heating, Cooling and DHW 		Heating, Cooling and DHW 		Heating and DHW 	Heating, Cooling and DHW 		
Energy Label Space Heating 35°C LWT									
Operation Range	Outdoor Air	-25 ~ 35°C	-25 ~ 35°C	-25 ~ 35°C	-20 ~ 35°C	-25 ~ 35°C	-20 ~ 35°C		
	Leaving Water	15 ~ 65°C	15 ~ 65°C	15 ~ 65°C	15 ~ 57°C	25 ~ 80°C	25 ~ 58°C		
Customer Needs	Designer & Installer	<ul style="list-style-type: none"> <li>- Space heating and cooling, domestic hot water, pool heating</li> <li>- Using existing facilities for conventional boiler</li> <li>- Saving installation and commissioning time</li> <li>- No Indoor Unit</li> </ul>		<ul style="list-style-type: none"> <li>- Space heating and cooling, domestic hot water, pool heating</li> <li>- Using existing facilities for conventional boiler</li> <li>- Minimized Wiring works</li> <li>- Eliminating the freezing risk at exposed water piping</li> </ul>		<ul style="list-style-type: none"> <li>- Space heating, domestic hot water</li> <li>- Using existing facilities (Old radiators)</li> <li>- Solution for poor insulated or old house</li> <li>- High DHW temperature to meet sanitary water regulation</li> </ul>		<ul style="list-style-type: none"> <li>- Space heating and cooling, domestic hot water</li> <li>- Saving installation time</li> <li>- Where mechanical room is very limited</li> </ul>	
	End-User	<ul style="list-style-type: none"> <li>- Low operation cost</li> <li>- Reliable operation and long lifetime</li> <li>- Easy and intuitive controls</li> <li>- Control integration between boiler and THERMA V</li> <li>- Remote Control by smartphone</li> <li>- Quiet operation</li> </ul>		<ul style="list-style-type: none"> <li>- Low operation cost</li> <li>- Reliable operation and long lifetime</li> <li>- Easy and intuitive controls</li> <li>- Control integration between boiler and THERMA V</li> <li>- Remote Control by smartphone</li> <li>- Quiet operation</li> </ul>		<ul style="list-style-type: none"> <li>- Low operation cost</li> <li>- Reliable operation and long lifetime</li> <li>- Easy and intuitive controls</li> <li>- Remote Control by smartphone</li> <li>- Quiet operation</li> </ul>		<ul style="list-style-type: none"> <li>- Low operation cost</li> <li>- Reliable operation and long lifetime</li> <li>- Necessity to install indoor unit in living space due to Insufficient machine room space</li> <li>- Quiet operation</li> </ul>	
LG Approach		<ul style="list-style-type: none"> <li>- All in one concept (No refrigerant piping work)</li> <li>- High energy efficiency</li> <li>- High corrosion resistance heat exchanger</li> <li>- New interface (RS3 remote controller)</li> <li>- Interlocking operation with 3<sup>rd</sup> party boiler</li> <li>- LG own Wi-Fi control solution (LG ThinQ)</li> <li>- Easy commissioning by PC tool (LG heating configurator)</li> <li>- Low noise mode operation with schedule setting</li> <li>- THERMA V Silent Monobloc</li> </ul>		<ul style="list-style-type: none"> <li>- High energy efficiency</li> <li>- High corrosion resistance heat exchanger</li> <li>- New interface (RS3 remote controller)</li> <li>- Interlocking operation with 3<sup>rd</sup> party boiler</li> <li>- LG own Wi-Fi control solution (LG ThinQ)</li> <li>- Easy commissioning by PC tool (LG heating configurator)</li> <li>- Placing hydronic components and water piping in the mechanical room</li> <li>- Low noise mode operation with schedule setting</li> </ul>		<ul style="list-style-type: none"> <li>- Max 80°C LWT by Cascade 2 stage compression (R410A - R134a)</li> <li>- Suitable for old radiator</li> <li>- High energy efficiency</li> <li>- High corrosion resistance heat exchanger</li> <li>- New interface (RS3 remote controller)</li> <li>- LG own Wi-Fi control solution (LG ThinQ)</li> <li>- Low noise mode operation with schedule setting</li> </ul>		<ul style="list-style-type: none"> <li>- All in one concept (Integrated DHW tank with indoor unit)</li> <li>- High energy efficiency</li> <li>- High corrosion resistance heat exchanger</li> <li>- Sophisticated and harmonious exterior of indoor unit</li> <li>- Placing hydronic components and water piping in the mechanical room</li> <li>- Low noise mode operation with schedule setting</li> </ul>	
Benefit		<ul style="list-style-type: none"> <li>- Multiple solution providing space heating and cooling, DHW supply</li> <li>- Energy saving by utilizing renewable energy and high efficient equipment</li> <li>- Simple replacement of existing boiler while maintaining the existing heating system</li> <li>- Hybrid operation with existing facilities</li> <li>- Quick &amp; easy installation and commissioning</li> <li>- Saving mechanical room space</li> <li>- Economic support by incentive program</li> </ul>		<ul style="list-style-type: none"> <li>- Multiple solution providing space heating and cooling, DHW supply</li> <li>- Energy saving by utilizing renewable energy and high efficient equipment</li> <li>- Free of freezing risk against exposed water piping even long black out</li> <li>- Hybrid operation with existing facilities</li> <li>- Quick &amp; easy installation and commissioning</li> <li>- Economic support by incentive program</li> </ul>		<ul style="list-style-type: none"> <li>- Multiple solution providing space heating and cooling, DHW supply</li> <li>- Energy saving by utilizing renewable energy and high efficient equipment</li> <li>- Obtaining 80°C high temperature water without supplementary heater</li> <li>- Simple replacement of existing boiler while maintaining the existing radiators</li> <li>- Economic support by incentive program</li> </ul>		<ul style="list-style-type: none"> <li>- Multiple solution providing space heating and cooling, DHW supply</li> <li>- Energy saving by utilizing renewable energy and high efficient equipment</li> <li>- Use of valuable machine room space for private purpose</li> <li>- Economic support by incentive program</li> </ul>	

# LINE UP OVERVIEW

Type	Refrigerant	Line-up	Capacity(kW)	5	7		
Monobloc	R32	R32 Monobloc	1Ø 230V	HM051M U43 	HM071M U43 		
			3Ø 400V				
		R32 Silent Monobloc	1Ø 230V				
Split	R32	R32 Split	1Ø 230V	HN0916M NK4 	HN0916M NK4 		
				HU051MR U44 	HU071MR U44 		
		R410A	R410A Split	1Ø 230V			
				3Ø 400V			
	R410A	R410A IWT	R410A IWT	1Ø 230V			
				3Ø 400V			
			High Temperature	High Temperature	1Ø 230V		
	Floor Standing	R410A + R134a	High Temperature	1Ø 230V			

9	12	14	16
HM091M U43 	HM121M U33 	HM141M U33 	HM161M U33 
	HM123M U33 	HM143M U33 	HM163M U33 
<b>NEW</b> HM091MRS U33 			
HN0916M NK4 			
HU091MR U44 			
	HN1616 NK3 	HN1616 NK3 	HN1616 NK3 
	HU121 U33 	HU141 U33 	HU161 U33 
	HN1639 NK3 	HN1639 NK3 	HN1639 NK3 
	HU123 U33 	HU143 U33 	HU163 U33 
HN1616T NB0 	HN1616T NB0 	HN1616T NB0 	HN1616T NB0 
HU091 U43 	HU121 U33 	HU141 U33 	HU161 U33 
	HN1616T NB0 	HN1616T NB0 	HN1616T NB0 
	HU123 U33 	HU143 U33 	HU163 U33 
			HN1610H NK3 
			HU161HA U33 



# LINE UP INTRODUCTION



## THERMA V R32 Monobloc

Monobloc is a fully packaged piece of equipment, where the indoor and outdoor units are combined as one module. Therefore, there is no need for refrigerant piping work since Monobloc unit located outside is connected only to water piping. Further, hydronic components such as plate heat exchanger, expansion tank and water pump are included in the package.

LG's THERMA V R32 Monobloc is designed to guarantee incomparable customer values including unbeatable energy efficiency, the ultimate in convenience, and easy controls by applying the advanced technologies. As it applies the low Global Warming Potential (GWP) R32 refrigerant and LG's exclusive R1 compressor to help it provide the powerful and high efficient heating. Furthermore, Thanks to a Wi-Fi modem and LG's smartphone app, LG ThinQ, users can monitor and remotely control compatible LG products, and access the vast majority of functions.



## THERMA V Silent Monobloc

LG's THERMA V R32 Silent Monobloc is designed for lower noise levels than conventional Monobloc series while retaining its previous advantages; All in one with eco-conscious R32 refrigerant and LG's powerful yet stable R1 compressor.

Thanks to its low noise level corresponding with DACH region noise regulations, THERMA V R32 Silent Monobloc offers maximized installation flexibility which allows installing within minimum safety space as 5m from neighboring houses. Moreover, the energy efficiency of THERMA V R32 Silent Monobloc is remarkably enhanced compared to conventional Monobloc as so it is recognized as an ultra-high efficient model.



## THERMA V R32 Split

Split is a hydro box type which is that the indoor unit and outdoor unit are separated. Between two units are connected by refrigerant piping only, thus hydronic components such as plate heat exchanger, expansion tank and water pump are located inside of the indoor unit. For that reason, it is easy to withstand freezing issues regardless of outside ambient temperature.

LG's THERMA V R32 Split designed specifically for the new and renovated housing markets is LG's highly-efficient product that can deliver effective space heating and hot water supply, as it applies the low Global Warming Potential (GWP) R32 refrigerant and LG's exclusive R1 compressor to help it provide the powerful and high efficient heating. Furthermore, Thanks to a Wi-Fi modem and LG's smartphone app, LG ThinQ, users can monitor and remotely control compatible LG products and access the vast majority of functions.



## THERMA V R410A Split

Split is a hydro box type which is that the indoor unit and outdoor unit are separated. Between two units are connected by refrigerant piping only, thus hydronic components such as plate heat exchanger, expansion tank and water pump are located inside of the indoor unit. For that reason, it is easy to withstand freezing issues regardless of outside ambient temperature.

LG's THERMA V R410A Split is designed for the benefit of the users and installers who want to apply with large capacity in colder climate conditions. As it has maximized energy efficiency (A++) in the mid-temperature ranges which leads to optimize and reduce operating costs.



## THERMA V IWT

IWT (Integrated Water Tank) is an integrated unit that indoor unit is combined with a domestic hot water tank while outdoor unit is separately located outside. THERMA V IWT is more suitable for the house which has less indoor spaces because hydronic components such as DHW tank and buffer tank normally installed additionally are integrated as one unit.

LG's THERMA V IWT is providing generous benefits supported by LG THERMA V's powerful and durable outdoor units.



## THERMA V High Temp

THERMA V high temperature is a kind of split type that consists of an indoor unit and an outdoor unit. Thanks to the cascade 2 stage compression technology, it can supply such high leaving water temperature - 80°C with high energy efficiency.

LG's THERMA V high temperature is suitable for houses which have poor insulation or existing old radiator or have to meet sanitary water regulation which requires high water temperature.




**THERMAV™**  
**FEATURES**

# FEATURE OVERVIEW

## LG THERMA V's Unique Features

LG THERMA V has been designed for providing efficient space heating and domestic hot water heating with usage convenience to the customer. To achieve this ultimate goal, LG has been developed and applied core technologies and functions for heating to the LG THERMA V.



## User Convenience


LG THERMA V is equipped with various user convenience function which are able to use it more easily and comfortably. The RS3 remote controller allows the user to control intuitively since it has a text based user friendly interface. A wide connectivity and lots of control options also provide user control convenience.

## Excellent Performance & Efficiency

LG THERMA V provides world-class energy efficiency by adopting LG's revolutionary technology such as R1 compressor, black fin heat exchanger. LG has been achieved a high heating performance even extremely cold weather condition and LG THERMA V can bring customers peace of mind through product reliability.

## Easy Installation & Maintenance

LG THERMA V offers installation and design flexibility to the installers. Installer also can minimize the spending time to perform commissioning by using LG heating configurator. Even during maintenance, the clip type connection allows fast and easy disassemble of the components.




# EXCELLENT PERFORMANCE & EFFICIENCY



## R1 Compressor

\* Applied model : R32 Series




### Shaft-through structure & Support both ends of shaft

- Solid compressor operation assuring higher durability



### Centrifugal oil return & Oil separating guide for oil discharge reduction

- Higher energy efficiency (\*SEER 20% ↑)



### Extended operation range (Max 150Hz)

- Higher heating performance




### Bottom compression & Simple structure

- Lower noise & vibration (\*\*Max 4dB(A) ↓)
- Less weight (\*\*20% ↓)
- Superior reliability

R1 Compressor™

\* LG Internal test result, Based on single split 10kW cassette.  
 \*\* LG Internal test result, Based on conventional compressor. (Rotary type GPT442M)

R1 Compressor is applied for high efficiency and reliability. This compressor is more advanced compared to the conventional one. Especially tilting motion of scroll has been improved. Further, the operation range is improved compared to the conventional type.




- Scroll compressor with simple structure.
- High efficiency. (Low load at low speed / Total efficiency)
- Low noise. (High speed possible)
- Improved tilting motion of scroll.
- 20% weight reduction. (vs. Conventional compressor)

\* Applied models : R32 Monobloc (5 - 16kW), R32 split (5 - 9kW)

## Seasonal Energy Efficiency


SEER 20%, SCOP 13% improvement. (vs. Rotary)



\* LG Internal test result, Based on single split 10kW CST.

## Wide Operation Range

- Optimized for various cooling & Heat load operation.
- World best compressor speed. (Up to 150Hz)
- Optimized for even low load operation. (Down to 10Hz) (Efficiency increases / Improved comfort)



# EXCELLENT PERFORMANCE & EFFICIENCY

## R32 Low GWP Refrigerant R32

\* Applied model : R32 Series

### Background

Due to accelerated global warming and the destruction of the ozone layer, various international conventions and meetings are held to enhance restrictions to the use of refrigerant or enforce the use of eco-conscious refrigerant. R32 is internationally acclaimed for being Eco-friendly. This low volume refrigerant is as efficient as any conventional refrigerant but boasts a 68% reduced global warming potential.



### Comparison & Benefit


R32 efficiently works even in small volume compared to existing R410A refrigerant, which decreases potential hazard of global warming. Furthermore, R32 refrigerant is easy to recycle thanks to single composition.

Description	R32	R410A
GWP Global Warming Potential	675	2088
Less Amount Gas Charge		
More System Performance	R32 systems also use less refrigerant per kilowatt of capacity delivered.	
Easy Refrigerant Recycle	Single component	Mixture R32 50% / R125 50%
High Capacity	High refrigerant compression rates lead to high capacity as compared to existing refrigerant R22 and R410A.	

## Flash Gas Injection

\* Applied model : R32 Series


In case of R32 refrigerant, it is very important to control discharge temperature of compressor properly. In the R32 Monobloc, flash gas injection technology is applied to control discharge temperature of compressor efficiently. As a result of this technology, heating operation range is expanded and heating performance at low ambient temperature is enhanced.



## Wide Operation Range

\* Applied model : R32 Series

Thanks to the Leaving Water Temperature (LWT) up to 65°C, temperature range requiring mid temperature radiator can be fully covered by THERMA V R32 Series. As a result, they have high competitiveness for replacement case as well as new house.





# EXCELLENT PERFORMANCE & EFFICIENCY

## Black Fin

\* Applied model : R32 Series

The black coating with enhanced epoxy resin is applied for strong protection from various corrosive external conditions such as salt contamination and air pollution including fumes from factories. This improvement in durability prolongs the product's lifespan and lowers both the operational and maintenance costs.

 **Longer Lifespan, Lower Operational Costs**

 **Strengthened corrosion resistant coating**

## Black Fin


### Hydrophilic Film (Water Flow)

The Hydrophilic coating minimizes moisture build up on the fin.

### Acryl + Epoxy + Melamine Resin (Corrosion Resistant)

The Black coating provides strong protection from corrosion.

### Aluminum Fin




## SST (Salt Spray Test)

### • Test Process



Test process is conducted according to ISO 9227.  
1) Salty water concentration : NaCl aqueous solution (5%)


### • Test Result (5% Area of defects compared to initial)



100% copper material to prevent corrosion & refrigerant leakage


## CCT (Cyclic Corrosion Test)

### • Test Process



Test process is conducted according to ISO 14933.  
1) Salty water concentration : NaCl aqueous solution (5%)  
2) Deionized water  
※ Dry condition changed : 60°C, 4hr → 70°C, 2hr

### • Test Result (5% Area of defects compared to initial)




100% copper material to prevent corrosion & refrigerant leakage

## Combination with Solar Thermal System

\* Applied model : R32 Series, R410A Split Hydro Box

THERMA V can combine with the Solar thermal system enabling heats up DHW tank. It measures the temperature difference between the solar collector and DHW tank, then it starts heat up if the solar collector temperature is higher than DHW tank.



\* Mandatory accessory : Solar Thermal Kit (PHLLA)

## Energy State

\* R32 Silent Monobloc R32 split, R410 split and High Temp. models has limited energy state function (ES1 - ES4 only). For more detail, please refer to the installation manual.

THERMA V is operated automatically according to the power supply status signals received from power supplying companies. This function can respond to European countries' special tariff for heat pump application on smart grids.

Energy States	Contact States		Power Supply Status	Operating Mode
	TB_SG1	TB_SG2		
ES1	1 : 0	●		<b>[Switch-off command, Utility lock]</b> Deactivates the heat pump to avoid peak load. The maximum blocking time depends on the power supply company. (Frost protection available)
ES2	0 : 0			<b>[Normal Operation]</b> The heat pump works at maximum efficiency.
ES3	0 : 1	●		<b>[Switch-on recommendation]</b> The switch-on recommendation and set value of target temperature is increased. (Heating +2°C / DHW +5°C)
ES4	1 : 1	●		<b>[Switch-on command]</b> Switch-on command. The set value of DHW temperature is set to 80°C and electric heaters can be activated.
ES5	The contact signal of 0 : 1 and 1 : 1 is designated ES3 and ES4 respectively as a default.		The set value of target temperature is changed. (Heating +5°C / Cooling -5°C / DHW +30°C)	
ES6	But ES3 (0 : 1) and ES4 (1 : 1) can be changed to ES5 - ES8 in installer setting. And the offset values of heating, cooling and DHW are changeable.		The set value of target temperature is changed. (Heating +2°C / Cooling -2°C / DHW +10°C)	
ES7			The set value of target temperature is changed. (Heating -2°C / Cooling +2°C)	
ES8			The set value of target temperature is changed. (Heating -5°C / Cooling +5°C)	

# USER CONVENIENCE



## Controller with Intuitive Interface

\* Applied model : R32 Series, R410A Split Hydro Box, High Temp


THERMA V is equipped with new remote controller which supports various functions.

### Premium Design

- New modern design 4.3 inch color LCD display.
- Capacitive touch button.  
(Especially On/Off button turn on LED)

### User Friendly Interface

- Information displayed with simple graphic, icon & text.
- Navigation button, easy to use.



### Enhanced Energy Information with Simple Interface

- A clear view of instantaneous power consumption against target.
- Accumulated power consumption and produced heat energy per week, month or year.



### Convenient Functions


- Optimize schedule setting logic.  
- Set the period, date, On/Off time, operation mode, target temp easy installation setting.



## LG Own Wi-Fi Solution

\* Applied model : R32 Series, R410A Split Hydro Box, High Temp

Access your THERMA V anytime from anywhere.



\* Search "LG ThinQ" on Google market or App store, then download the app.

### Simple Operation for Various Functions

- On/Off
- Operation mode selection
- Current temperature
- Set temperature
- On/Off reservation
- Energy monitoring



Mandatory accessory :  
PWFMD200 (LG Wi-Fi modem) and  
PWYREW000 (10m extension connect cable  
in between THERMA V indoor and Wi-Fi modem)

# USER CONVENIENCE


## 2<sup>nd</sup> Circuit

\* Applied model : R32 Series, R410A Split Hydro Box

2 Zones (Add / Main zone) temperature control through separate heating circuits is possible with mixing valve kit.

### 2 Zones Temperature Control

### 2<sup>nd</sup> Circuit Diagram




## Various Temperature Control Options

\* Applied model : R32 Series, R410A Split Hydro Box, High Temp

Various temperature control options are possible for the user's comfort and convenience. Especially for European life style where thermal comfort is preferred, simultaneous control option is newly added. (Room air + Water temperature)

- Control based on leaving water temperature.
  - Control based on entering water temperature.
  - Control based on room air temperature.
  - Control based on room air and water temperature simultaneously.
- Thermo On : When satisfied both room air temp condition and water temp condition  
 - Thermo Off : When satisfied room air temp condition or water temp condition





# USER CONVENIENCE

## Built-in Flow Sensor

\* Applied model : R32 Split

Flow sensor provides the actual flow rate information in a display of wired remote controller.

- Flow sensor type : Vortex
- Measuring duration : 1s




## Improved Flow Switch

\* Applied model : All Line-up except R32 Split

By applying the magnetic type of flow switch, the field trouble occurrence related to water flow switch will be decreased.

- No contact between sensing part (magnet) and water



## Interlocking Operation with 3<sup>rd</sup> Party Boiler



\* Applied model : R32 Series, R410A Split Hydro Box

3<sup>rd</sup> Party boiler can be activated by the R32 Split controller as an auxiliary equipment of AHWP.

### Control Mode : Auto / Manual

- Auto control mode :  
In order to protect THERMA V, 3<sup>rd</sup> party boiler is automatically activated when outdoor temperature is lower than certain temperature instead of THERMA V. (Default : -7°C, Range : -25 ~ 15°C)
- Manual control mode :  
User can manually operate 3<sup>rd</sup> party boiler via RS3 remote controller as needed.

### Auto Control Mode




\* 3<sup>rd</sup> party boiler should have a water pump integrated with it.

## Energy Information Monitoring

\* Applied model : All Line-up except R410A IWT

Power consumption and heat provided by the AWHP can be measured and monitored on the remote controller using meter interface.



\* Mandatory accessory : PENKTH000 (Meter Interface)

Instantaneous Power		Usage Rate	
Target	10 kW	Usage Rate	
Current	0 kW	0%	
Total	16 kW		

Year on Year Usage	
Power	Calorie
2020.05	2019.05
2020.05	2020.05
Year on Year Growth	
0%	


# USER CONVENIENCE

## Seasonal Auto Mode

\* Applied model : R32 Series, R410A Split Hydro Box

In this mode, the target temperature will vary according to the outdoor temperature automatically. This mode adds the cooling season function to the conventional weather dependent operation mode.



Setting	Description	R410A Product Range	R410A Product Default	R32 Product Range	R32 Product Default
A1	Lowest Ambient Temp	Fix	-15°C	Fix	-25°C
A2	Heating Lower Ambient Temp	-15 ~ 24°C	-10°C	-25 ~ 35°C	-10°C
A3	Heating Higher Ambient Temp	-15 ~ 24°C	16°C	-25 ~ 35°C	16°C
A4	Cooling Lower Ambient Temp	10 ~ 43°C	30°C	10 ~ 46°C	30°C
A5	Cooling Higher Ambient Temp	10 ~ 43°C	40°C	10 ~ 46°C	40°C
A6	Highest Ambient Temp	Fix	43°C	Fix	46°C
LW1	Heating Highest Water Temp	15 ~ 57°C	57°C	15 ~ 65°C	65°C
LW2	Heating Higher Water Temp	15 ~ 57°C	35°C	15 ~ 65°C	35°C
LW3	Heating Lower Water Temp	15 ~ 57°C	28°C	15 ~ 65°C	28°C
LW4	Cooling Higher Water Temp	5 ~ 25°C	20°C	5 ~ 27°C	20°C
LW5	Cooling Lower Water Temp	5 ~ 25°C	16°C	5 ~ 27°C	18°C
LW6	Cooling Lowest Water Temp	5 ~ 25°C	16°C	5 ~ 27°C	18°C
RA1	Heating Highest Air Temp	16 ~ 30°C	30°C	16 ~ 30°C	30°C
RA2	Heating Higher Air Temp	16 ~ 30°C	30°C	16 ~ 30°C	30°C
RA3	Heating Lower Air Temp	16 ~ 30°C	26°C	16 ~ 30°C	26°C
RA4	Cooling Higher Air Temp	18 ~ 30°C	22°C	16 ~ 30°C	22°C
RA5	Cooling Lower Air Temp	18 ~ 30°C	18°C	16 ~ 30°C	18°C
RA6	Cooling Lowest Air Temp	18 ~ 30°C	18°C	16 ~ 30°C	18°C



## Low Noise Mode & Scheduler

\* Applied model : All Line-up except High Temp


Low Noise mode operation can reduce the noise level by remote controller and users can set the weekly On / Off schedule.



## Screed Drying Program

\* Applied model : R32 Series, R410A Split Hydro Box

THERMA V has an automatic program for drying out the screed of an underfloor heating system during the construction of a house.




Step	1	2	3	4	5	6	7	8	9	10	11
Leaving Water Target Temperature (°C)	25	Max T	Off	25	35	45	Max T	Max T	45	35	35
Duration (Hours)	72	96	72	24	24	24	24	Holding Time	72	72	72

## 2 Remote Control

\* Applied model : All Line-up except R410A IWT

Convenient control by installing additional RS3 at living room.

### System Diagram




\* Master is for the installation setting.  
\* Slave is for user setting.

### RS3 UI

• THERMA V is operating based the room where slave RS3 is installed.

: Room air temperature sensed by slave RS3 remote controller




# EASY INSTALLATION & MAINTENANCE

## LG Heating Configurator

\* Applied model : R32 Series, R410A Split Hydro Box

### Easy Installation Setting and Commissioning


- Based on installation site information, installers can prepare presetting with LG heating configurator and save data into memory card from office.
- At the site, then installers can simply insert memory card at the back of remote controller to activate configuration data.



## Clip Type Connection for Easy Maintenance

\* Applied model : R32 Series, R410A Split Hydro Box


- Easy access to water pump and strainer. (Front panel)
- Clip type connection for components.



## Flexible Refrigerant Piping Design



\* Applied model : R32 Split, R410A Split, R410A IWT, High Temp

Long piping length and 3way piping enable flexible design and easy installation.






**THERMAV™**  
**PRODUCTS**




## Excellent Performance & Efficiency



## User Convenience




## Easy Installation & Maintenance



\* Detailed description for each function is presented on page 22 - 37.



## Energy Labeling



\* 16kW 1Ø model.  
\* A+++ to D scale.

## Monobloc Concept

Monobloc is a fully packaged piece of equipment, where the indoor and outdoor units are combined as one module. Therefore, there is no need for refrigerant piping work since Monobloc unit located outside is connected only to water piping. Further, hydronic components such as plate heat exchanger, expansion tank and water pump are included in the package.




## Capacity Range (Heating & Cooling)

### Monobloc

Capacity Range [kW]	5	6	7	8	9	10	11	12	13	14	15	16	17
Heating Capacity	●		●		●			●		●		●	
Cooling Capacity	●		●		●			●		●		●	

## Operation Range (Heating & Cooling)




# THERMA V™ R32 MONOBLOC

## PRODUCT FEATURES

### All in One Concept


Thanks to all in one concept and reduced weight, easier & quicker installation is possible.

- LG provides fully packaged THERMA V Monobloc that additional water side components are included in the package.
- No need to work refrigerant piping, easier and quicker installation.



### High Heating Performance even at Low Temperature


The R32 Monobloc provides excellent heating performance – especially at low ambient temperature. Heating capacity of R32 Monobloc at low ambient temperature is improved more than 20% compared to R410A Monobloc.



Note  
1. LWT : Leaving Water Temperature, OAT : Outdoor Air Temperature.


### High Energy Efficiency

The energy label directive is a key factor of selecting heating device in Europe heating market. The R32 Monobloc type has an energy label rating over A+++ in ErP energy labeling regulation.



### Reduced Noise Level


The R32 Monobloc reduces noise level compared to previous models.



# PRODUCT SPECIFICATION

## Monobloc

HM051M U43  
HM071M U43  
HM091M U43



## Features

- High energy efficiency (SCOP4.45 / A+++)
- Excellent performance at low ambient temperature (100% @ -7°C)
- Wide operation range (Ambient: -25 ~ 35°C / Water side: 15 ~ 65°C)
- R32 Refrigerant with low GWP
- R1 Scroll compressor
- Corrosion resistance black fin
- LG ThinQ
- KEYMARK / EHPA certification / MCS / Eurovent certification

## Model Line up

Category	Unit	Model Name		
		Capacity (kW)		
		5.5	7.0	9.0
1 Phase Model 220 - 240V, 1Ø, 50Hz	Monobloc Unit	HM051M U43	HM071M U43	HM091M U43

## Seasonal Energy

Description		Unit	HM051M U43	HM071M U43	HM091M U43	
Space Heating (According to EN14825)	Average Climate Water Outlet 35°C	SCOP	W/W	4.45	4.45	4.45
		Rated Heat Output (P <sub>rated</sub> )	kW	5	6	6
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	175	175	175
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A+++	A+++	A+++
		Annual Energy Consumption	kWh	2,551	2,668	2,784
	Average Climate Water Outlet 55°C	SCOP	-	3.12	3.12	3.12
		Rated Heat Output (P <sub>rated</sub> )	kW	5	5	5
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	122	122	122
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A+	A+	A+
		Annual Energy Consumption	kWh	3,638	3,638	3,638

## Nominal Capacity and Nominal Input

Description	OAT (DB)	LWT (DB)	Unit	HM051M U43	HM071M U43	HM091M U43		
Nominal Capacity	Heating	7°C	35°C	kW	5.50	7.00	9.00	
		7°C	55°C		5.50	5.50	5.50	
	Cooling	2°C	35°C		3.30	4.20	5.40	
		35°C	18°C		5.50	7.00	9.00	
Nominal Power Input	Heating	7°C	35°C	kW	1.22	1.56	2.15	
		7°C	55°C		2.04	2.04	2.04	
	Cooling	2°C	35°C		0.94	1.20	1.54	
		35°C	18°C		1.20	1.56	2.14	
	COP	Heating	35°C		7°C	1.96	2.59	3.46
			7°C		35°C	4.50	4.50	4.18
EER	Cooling	7°C	55°C	W/W	2.70	2.70	2.70	
		2°C	35°C		3.52	3.51	3.50	
EER	Cooling	35°C	18°C	W/W	4.60	04.5	4.20	
		35°C	7°C		2.80	2.70	2.60	

## Product Specification

Technical Specification			Unit	HM051M U43	HM071M U43	HM091M U43	
Water Side	Operation Range (Leaving Water Temperature)	Heating	Min - Max	°CDB	15 - 65		
		Cooling			5 - 27 (16 - 27) <sup>2)</sup>		
		DHW <sup>1)</sup>			15 - 80		
	Piping Connections	Water Circuit	Inlet	mm (inch)	Male PT 25.4 (1)		
			Outlet	mm (inch)	Male PT 25.4 (1)		
Rated Water Flow Rate at LWT 35°C			l/min	15.81	20.12	25.87	
Refrigerant Side	Operation Range (Outdoor Temp)	Heating	Min - Max	°CDB	-25 - 35		
		Cooling			5 - 48		
	Compressor	Quantity	EA	1			
		Type	-	Hermetic Sealed Scroll			
	Refrigerant	Type	-	R32			
		GWP(Global Warming Potential)	-	675			
		Precharged Amount	g	1,400			
	t-CO <sub>2</sub> eq	-	0.945				
Sound Power Level		Heating	Rated	dB(A)	60		
Sound Pressure Level (at 1m)		Heating	Rated	dB(A)	50		
Dimensions		Unit	W x H x D	mm	1,239 x 834 x 330		
Weight		Unit	kg	91.0			
Power Supply		Voltage, Phase, Frequency		V, Ø, Hz	220 - 240, 1, 50		
		Maximum Running Current		A	14.2	15.7	23.0
		Recommended Circuit Breaker		A	16	20	25
Wiring Connections		Power Supply Cable (Included Earth, H07RN-F)		mm <sup>2</sup> x cores	4.0 x 3		

1) DHW 58 - 80°C Operating is available only when the booster heater is operating.  
2) When fan coil unit not used.

### Note




1. Due to our policy of innovation some specifications may be changed without notification.
2. Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.
3. Sound pressure level is measured on the rated condition in the anechoic rooms by ISO 3745 standard. Sound power level is measured on the rated condition in the reverberation rooms by ISO 3741 standard. Therefore, these values can be increased owing to ambient conditions during operation.
4. Performances are accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions acc. ErP regulation. For max capacities, refer to Performance Data.  
• Rated running current : Outdoor Temp 7°CDB / 6°CWB, LWT 35°C
5. This product contains Fluorinated greenhouse gases.

# PRODUCT SPECIFICATION





## Drawings

Category	Unit	Model Name		
		5.5	7.0	9.0
1 Phase Model 220 - 240V, 1Ø, 50Hz	Monobloc Unit	HM051M U43	HM071M U43	HM091M U43

[Unit : mm]



Side View



3D View


No.	Part Name	Description
1	Entering Water Pipe	Male PT 1 inch
2	Leaving Water Pipe	Male PT 1 inch
3	Strainer	Filtering and stacking particles inside circulating water
4	Top Cover	-
5	Front Panel	-
6	Side Panel	-
7	Low Voltage	Accessory kit cables
8	Unit Power	Outdoor entry power cable
9	Water Pump	-
10	Plate Heat Exchanger	Heat exchange between refrigerant and water
11	Pressure Gauge	Indicates circulating water pressure
12	Safety Valve	Open at water pressure 3bar
13	Indoor Control Box	Indoor PCB and terminal blocks
14	Outdoor Control Box	Outdoor PCB and terminal blocks



# PRODUCT SPECIFICATION

## Monobloc

- HM121M U33
- HM141M U33
- HM161M U33
- HM123M U33
- HM143M U33
- HM163M U33



### Features

- High energy efficiency (SCOP 4.45 / A+++)
- Excellent performance at low ambient temperature (100% @ -7°C)
- Wide operation range (Ambient : -25 ~ 35°C / Water side : 15 ~ 65°C)
- R32 Refrigerant with low GWP
- R1 Scroll compressor
- Corrosion resistance black fin
- LG ThinQ
- KEYMARK / EHPA certification / MCS / Eurovent certification

Note  
1. Approved model by EHPA : HM123M U33, HM143M U33, HM163M U33.

### Model Line up

Category	Unit	Model Name		
		Capacity (kW)		
		12.0	14.0	16.0
1 Phase Model 220 - 240V, 1Ø, 50Hz	Monobloc Unit	HM121M U33	HM141M U33	HM161M U33
		HM123M U33	HM143M U33	HM163M U33

### Seasonal Energy

Description		Unit	HM121M U33 HM123M U33	HM141M U33 HM143M U33	HM161M U33 HM163M U33	
Space Heating (According to EN14825)	Average Climate Water Outlet 35°C	SCOP	W/W	4.45	4.45	4.45
		Rated Heat Output (P <sub>rated</sub> )	kW	10	11	11
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	175	175	175
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A+++	A+++	A+++
		Annual Energy Consumption	kWh	4,642	4,875	5,103
	Average Climate Water Outlet 55°C	SCOP	-	3.18	3.18	3.18
		Rated Heat Output (P <sub>rated</sub> )	kW	12	12	12
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	124	124	124
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A+	A+	A+
		Annual Energy Consumption	kWh	7,795	7,795	7,795

### Nominal Capacity and Nominal Input

Description		OAT (DB)	LWT (DB)	Unit	HM121M U33 HM123M U33	HM141M U33 HM143M U33	HM161M U33 HM163M U33
Nominal Capacity	Heating	7°C	35°C	kW	12.00	14.00	16.00
		7°C	55°C		12.00	12.00	12.00
	2°C	35°C	11.00		12.00	13.80	
	2°C	55°C	12.00		14.00	16.00	
Nominal Power Input	Heating	7°C	35°C	kW	2.61	3.11	3.64
		7°C	55°C		4.29	4.29	4.29
	2°C	35°C	3.13		3.42	3.94	
	2°C	55°C	3.13		3.42	3.94	
COP	Heating	7°C	35°C	W/W	4.60	4.50	4.40
		7°C	55°C		2.80	2.80	2.80
	2°C	35°C	3.52		3.51	3.50	
	2°C	55°C	3.52		3.51	3.50	
EER	Cooling	35°C	18°C	W/W	4.60	4.30	4.00
		35°C	7°C		2.70	2.60	2.50

### Product Specification

Technical Specification			Unit	HM121M U33	HM141M U33	HM161M U33	HM123M U33	HM143M U33	HM163M U33
Water Side	Operation Range (Leaving Water Temperature)	Heating	Min - Max	°CDB	15 - 65				
		Cooling			5 - 27 (16 - 27) <sup>2)</sup>				
		DHW <sup>1)</sup>			15 - 80				
	Piping Connections	Water	Inlet	mm (inch)	Male PT 25.4 (1)				
		Circuit	Outlet	mm (inch)	Male PT 25.4 (1)				
Rated Water Flow Rate at LWT 35°C			l/min	34.50	40.25	46.00	34.50	40.25	46.00
Refrigerant Side	Operation Range (Outdoor Temp)	Heating	Min - Max	°CDB	-25 - 35				
		Cooling			5 - 48				
	Compressor	Quantity	EA	1					
		Type	-	Hermetic Sealed Scroll					
	Refrigerant	Type	-	R32					
		GWP (Global Warming Potential)	-	675					
		Precharged Amount	g	2,400					
t-CO <sub>2</sub> eq			-	1,620					
Sound Power Level		Heating	Rated	dB(A)	63				
Sound Pressure Level (at 1m)		Heating	Rated	dB(A)	52				
Dimensions	Unit	W x H x D	mm	1,239 x 1,380 x 330					
Weight	Unit		kg	124.5					
Power Supply	Voltage, Phase, Frequency		V, Ø, Hz	220 - 240, 1, 50			380 - 415, 3, 50		
	Maximum Running Current		A	33.0	34.0	35.0	12.0	12.5	13.0
	Recommended Circuit Breaker		A	40			16		
Wiring Connections		Power Supply Cable (Included Earth, H07RN-F)	mm <sup>2</sup> x cores	6.0 x 3			4.0 x 5		



1) DHW 58 - 80°C Operating is available only when the booster heater is operating.  
2) When fan coil unit not used.

- Note
- Due to our policy of innovation some specifications may be changed without notification.
  - Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.
  - Sound pressure level is measured on the rated condition in the anechoic rooms by ISO 3745 standard. Sound power level is measured on the rated condition in the reverberation rooms by ISO 3741 standard. Therefore, these values can be increased owing to ambient conditions during operation.
  - Performances are accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions acc. ErP regulation. For max capacities, refer to Performance Data.
    - Rated running current : Outdoor Temp 7°CDB / 6°CWB, LWT 35°C
  - This product contains Fluorinated greenhouse gases.

# PRODUCT SPECIFICATION

## Drawings

Category	Unit	Model Name		
		12.0	14.0	16.0
1 Phase Model 220 - 240V, 1Ø, 50Hz	Monobloc Unit	HM121M U33	HM141M U33	HM161M U33
3 Phase Model 380 - 415V, 3Ø, 50Hz		HM123M U33	HM143M U33	HM163M U33




No.	Part Name	Description
1	Entering Water Pipe	Male PT 1 inch
2	Leaving Water Pipe	Male PT 1 inch
3	Strainer	Filtering and stacking particles inside circulating water
4	Top Cover	-
5	Front Panel	-
6	Side Panel	-
7	Low Voltage	Accessory kit cables
8	UNIT Power	Outdoor entry power cable
9	Water Pump	-
10	Plate Heat Exchanger	Heat exchange between refrigerant and water
11	Pressure Gauge	Indicates circulating water pressure
12	Safety Valve	Open at water pressure 3bar
13	Indoor Control Box	Indoor PCB and terminal blocks
14	Outdoor Control Box	Outdoor PCB and terminal blocks

# PRODUCT SPECIFICATION

## Electric Back up Heater

HA031M E1  
HA061M E1  
HA063M E1



## Product Specification



Electrical Specification		Unit	HA031M E1	HA061M E1	HA063M E1
Back up Heater	Type	-	Sheath		
	Number of Heating Coil	EA	1	2	3
	Capacity Combination	kW	3.0	3.0 + 3.0	2.0 + 2.0 + 2.0
	Operation	-	Automatic		
	Heating Steps	Step	1	2	1
	Power Supply	V, Ø, Hz	220 - 240, 1, 50		380 - 415, 3, 50
	Maximum Current	A	12.0	24.0	8.7
	Dimensions (W x H x D)	mm	210 x 607 x 220		
Net Weight (Unit)	kg	13.0	13.8	14.1	
Wiring Connections	Power Supply Cable (Included Earth, H07RN-F)	mm <sup>2</sup> x cores	1.5 x 3	4.0 x 3	2.5 x 4
	Communication Cable (H07RN-F)	mm <sup>2</sup> x cores	0.75 x 2	0.75 x 4	0.75 x 2

Note


1. Due to our policy of innovation some specifications may be changed without notification.
2. Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.

No.	Part Name	Description
1	Leaving Water Pipe	Male PT 1 inch
2	Entering Water Pipe	Male PT 1 inch
3	Control Box	Circuit breaker, Magnetic switch, Terminal blocks
4	Thermal Switch	Cut-off power input to E/Heater at 90°C
5	Air Vent	Air purging when charging water
6	Electric Heater	Refer the related information
7	Backup Heater Outlet Sensor (S13)	Connect to unit (Heat pump)

**NEW**  
**THERMA V™ R32**  
**SILENT MONOBLOC**




**Excellent Performance & Efficiency**



**User Convenience**




**Easy Installation & Maintenance**



\* Detailed description for each function is presented on page 22 - 37.

**Energy Labeling**



\* A+++ to D scale.

**Silent Monobloc Concept**

LG's THERMA V R32 Silent Monobloc is designed for lower noise levels than conventional Monobloc series while retaining its previous advantages; All in one with eco-conscious R32 refrigerant and LG's powerful yet stable R1 compressor. Thanks to its low noise level corresponding with DACH region noise regulations, THERMA V R32 Silent Monobloc offers maximized installation flexibility which allows installing within minimum safety space as 5m from neighboring houses.




**Capacity Range (Heating & Cooling)**

**Monobloc**

Capacity Range [kW]	5	6	7	8	9	10	11	12	13	14	15	16	17
Heating Capacity					●								
Cooling Capacity					●								

**Operation Range (Heating & Cooling)**




# THERMA V™ R32 SILENT MONOBLOC

## PRODUCT FEATURES


### Very Low Sound Level

With a sound level that is quieter than a library, THERMA V Silent Monobloc operates at 32dB(A) in Low noise mode, creating a tranquil environment indoors and outdoors.



### Installation Flexibility


THERMA V Silent Monobloc can be installed up to 4m (in Low noise mode) from neighboring houses while complying with noise regulations.



Noise Regulation	Germany (TA Lärm)		Austria (ÖNORM S 5021)	
	In Residential Area (Rest Area)	Day (06 - 22)	50dB(A)	Day (06 - 19)
Night (22 - 06)		35dB(A)	Evening (19 - 22)	40dB(A)
			Night (22 - 06)	35dB(A)


### High Energy Efficiency

The energy label directive is a key factor of selecting heating device in Europe heating market. THERMA V Silent Monobloc has an energy label rating A+++ for low temperature application and A++ for medium temperature application in ErP energy labeling regulation.



### High Heating Performance even at Low Temperature

THERMA V Silent Monobloc provides excellent heating performance – especially at low ambient temperature. Heating Capacity at OAT -7°CDB & LWT 35°C is same as normal capacity<sup>1)</sup> and Heating Capacity at OAT -15°CDB & LWT 35°C is more than 80% of normal capacity.



1) Normal : Outdoor air temperature 7°CDB / 6°CWB, Water outlet temperature 35°C

# PRODUCT SPECIFICATION

## Silent Monobloc

HM091MRS U33



### Features

- Very Low Sound Level (32dB(A) at 5m in low noise mode)
- High energy efficiency (SCOP 4.68 / A+++)
- Excellent performance at low ambient temperature (100% @ -7°C)
- Wide operation range (Ambient: -25 ~ 35°C / Water side: 15 ~ 65°C)
- R32 Refrigerant with low GWP
- R1 Scroll compressor
- Corrosion resistance black fin
- LG ThinQ
- KEYMARK / EHPA certification / MCS / Eurovent certification

### Model Line up

Category	Unit	Model Name	
		Capacity (kW)	
		9.0	
1 Phase Model 220 - 240V, 1Ø, 50Hz	Monobloc Unit	HM091MRS U33	

### Seasonal Energy

Description	Unit	HM091MRS U33		
Space Heating (According to EN14825)	Average Climate Water Outlet 35°C	SCOP	W/W	4.68
		Rated Heat Output (P <sub>rated</sub> )	kW	8
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	184
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A+++
		Annual Energy Consumption	kWh	3,533
	Average Climate Water Outlet 55°C	SCOP	-	3.33
		Rated Heat Output (P <sub>rated</sub> )	kW	8
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	130
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A++
		Annual Energy Consumption	kWh	4,971

### Nominal Capacity and Nominal Input

Description	OAT (DB)	LWT (DB)	Unit	HM091MRS U33			
Nominal Capacity	Heating	7°C	35°C	kW	9.00		
		7°C	55°C		6.00		
	Cooling	2°C	35°C		8.00		
		35°C	18°C		9.00		
Nominal Power Input	Heating	7°C	35°C	kW	1.76		
		7°C	55°C		2.14		
	Cooling	2°C	35°C		2.16		
		35°C	18°C		1.80		
	COP	Heating	7°C		35°C	W/W	5.10
			7°C		55°C		2.80
EER	Cooling	2°C	35°C	W/W	3.70		
		35°C	18°C		5.00		
		35°C	7°C		3.00		

### Product Specification

Technical Specification				Unit	HM091MRS U33
Water Side	Operation Range (Leaving Water Temperature)	Heating	Min - Max	°CDB	15 - 65
		Cooling			5 - 27 (16 - 27) <sup>2)</sup>
		DHW <sup>1)</sup>			15 - 80
	Piping Connections	Water Circuit	Inlet	mm (inch)	Male PT 25.4 (1)
			Outlet	mm (inch)	Male PT 25.4 (1)
Rated Water Flow Rate at LWT 35°C				l/min	25.87
Refrigerant Side	Operation Range (Outdoor Temp)	Heating	Min - Max	°CDB	-25 - 35
		Cooling			5 - 48
	Compressor	Quantity	EA	1	
		Type	-	Hermetic Sealed Scroll	
	Refrigerant	Type	-	R32	
		GWP(Global Warming Potential)	-	675	
		Precharged Amount	g	2,100	
	t-CO <sub>2</sub> eq	-	1,418		
Sound Power Level	Heating	Rated	dB(A)	57	
		Low noise		54	
Sound Pressure Level (at 1m)	Heating	Rated	dB(A)	35	
		Low noise		32	
Dimensions	Unit	W x H x D	mm	1,239 x 1,380 x 330	
Weight	Unit		kg	115.5	
Power Supply	Voltage, Phase, Frequency		V, Ø, Hz	220 - 240, 1, 50	
	Maximum Running Current		A	15.0	
	Recommended Circuit Breaker		A	16	
Wiring Connections	Power Supply Cable (Included Earth, H07RN-F)		mm <sup>2</sup> x cores	4.0 x 3	

1) DHW 58 - 80°C Operating is available only when the booster heater is operating.  
2) When fan coil unit not used.



Note

- Due to our policy of innovation some specifications may be changed without notification.
- Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.
- Sound pressure level is measured on the rated condition in the anechoic rooms by ISO 3745 standard. Sound power level is measured on the rated condition in the reverberation rooms by ISO 3741 standard. Therefore, these values can be increased owing to ambient conditions during operation.
- Performances are accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions acc. ErP regulation. For max capacities, refer to Performance Data.  
• Rated running current : Outdoor Temp 7°CDB / 6°CWB, LWT 35°C
- This product contains Fluorinated greenhouse gases.

# PRODUCT SPECIFICATION

## Drawings

Category	Unit	Model Name
		Capacity (kW)
1 Phase Model 220 - 240V, 1Ø, 50Hz	Monobloc Unit	HM091MRS U33




No.	Part Name	Description
1	Entering Water Pipe	Male PT 1 inch
2	Leaving Water Pipe	Male PT 1 inch
3	Strainer	Filtering and stacking particles inside circulating water
4	Top Cover	-
5	Front Panel	-
6	Side Panel	-
7	Low Voltage	Accessory kit cables
8	UNIT Power	Outdoor entry power cable
9	Water Pump	-
10	Plate Heat Exchanger	Heat exchange between refrigerant and water
11	Pressure Gauge	Indicates circulating water pressure
12	Safety Valve	Open at water pressure 3bar
13	Indoor Control Box	Indoor PCB and terminal blocks
14	Outdoor Control Box	Outdoor PCB and terminal blocks

# PRODUCT SPECIFICATION

## Electric Back up Heater

HA031M E1  
HA061M E1



## Product Specification



Electrical Specification		Unit	HA031M E1	HA063M E1
Back up Heater	Type	-	Sheath	
	Number of Heating Coil	EA	1	2
	Capacity Combination	kW	3.0	3.0 + 3.0
	Operation	-	Automatic	
	Heating Steps	Step	1	2
	Power Supply	V, Ø, Hz	220 - 240, 1, 50	
	Maximum Current	A	12.0	24.0
	Dimensions (W x H x D)	mm	210 x 607 x 220	
Net Weight (Unit)	kg	13.0	13.8	
Wiring Connections	Power Supply Cable (Included Earth, H07RN-F)	mm <sup>2</sup> x cores	1.5 x 3	4.0 x 3
	Communication Cable (H07RN-F)	mm <sup>2</sup> x cores	0.75 x 2	0.75 x 4

Note  
 1. Due to our policy of innovation some specifications may be changed without notification.  
 2. Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.

No.	Part Name	Description
1	Leaving Water Pipe	Male PT 1 inch
2	Entering Water Pipe	Male PT 1 inch
3	Control Box	Circuit breaker, Magnetic switch, Terminal blocks
4	Thermal Switch	Cut-off power input to E/Heater at 90°C
5	Air Vent	Air purging when charging water
6	Electric Heater	Refer the related information
7	Backup Heater Outlet Sensor (S13)	Connect to unit (heat pump)




# THERMA V™ R32 SPLIT HYDRO BOX TYPE




## Excellent Performance & Efficiency



## User Convenience




## Easy Installation & Maintenance



\* Detailed description for each function is presented on page 22 - 37.



## Energy Labeling



\* 9kW 1Ø model.  
\* A+++ to D scale.

## Split Hydro Box Concept

Split is a hydro box type which is that the indoor unit and outdoor unit are separated. Between two units are connected by refrigerant piping only, thus hydronic components such as plate heat exchanger, expansion tank and water pump are located inside of the indoor unit. For that reason, it is easy to withstand freezing issues regardless of outside ambient temperature.




## Capacity Range (Heating & Cooling)

### Split Hydro Box Type

Capacity Range [kW]	5	6	7	8	9	10	11	12	13	14	15	16	17
Heating Capacity	●		●		●								
Cooling Capacity	●		●		●								


## Operation Range (Heating & Cooling)



# PRODUCT FEATURES

## High Energy Efficiency


The energy label directive is a key factor of selecting heating device in Europe heating market. The R32 Split type has an energy label rating A+++ in ErP energy labeling regulation.



\* Test Condition  
Test procedure follows EN14825 (Low Temp average),  
Based on the single phase model line up.


## Reduced Noise Level

The R32 Split has a noise level as low as the conversation.



## High Heating Performance even at Low Temperature

The R32 Split provides excellent heating performance – especially at low ambient temperature. Heating capacity at OAT -7°CDB is same as normal capacity and heating capacity at OAT -15°CDB is more than 85% of normal capacity. Heating capacity of R32 Split at low ambient temperature is improved more than 18% compared to R410A Split.



# PRODUCT SPECIFICATION

## Split Hydro Box Type

### IDU


HN0916M NK4

### ODU

HU051MR U44

HU071MR U44

HU091MR U44



### Features

- High energy efficiency (SCOP 4.65 / A+++)
- Excellent performance at low ambient temperature (100% @ -7°C)
- Wide operation range (Ambient : -25 ~ 35°C / Water side : 15 ~ 65°C)
- R32 Refrigerant with low GWP
- R1 Scroll compressor
- Corrosion resistance black fin
- LG ThinQ
- KEYMARK / EHPA certification / MCS / Eurovent certification

### Model Line up

Category	Unit	Model Name Capacity (kW)		
		5.5	7.0	9.0
1 Phase Model 220 ~ 240V, 1Ø, 50Hz	Outdoor Unit	HU051MR U44	HU071MR U44	HU091MR U44
	Indoor Unit	HN0916M NK4		

### Seasonal Energy

Description		Outdoor Unit Indoor Unit	HU051MR U44	HU071MR U44 HN0916M NK4	HU091MR U44	
Space Heating (According to EN14825)	Average Climate Water Outlet 35°C	SCOP	-	4.65	4.65	4.65
		Rated Heat Output (P <sub>rated</sub> )	kW	6	6	6
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	183	183	183
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A+++	A+++	A+++
		Annual Energy Consumption	kWh	2,444	2,552	2,669
	Average Climate Water Outlet 55°C	SCOP	-	3.23	3.23	3.23
		Rated Heat Output (P <sub>rated</sub> )	kW	6	6	6
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	126	126	126
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A++	A++	A++
		Annual Energy Consumption	kWh	3,843	3,843	3,843

### Nominal Capacity and Nominal Input

Description		OAT (DB)	LWT (DB)	Outdoor Unit Indoor Unit	HU051MR U44	HU071MR U44 HN0916M NK4	HU091MR U44
Nominal Capacity	Heating	7°C	35°C	kW	5.50	7.00	9.00
		7°C	55°C		5.50	5.50	5.50
		2°C	35°C		3.30	4.20	5.40
	Cooling	35°C	18°C		5.50	7.00	9.00
		35°C	7°C		5.50	7.00	9.00
		7°C	35°C		1.12	1.43	1.94
Nominal Power Input	Heating	7°C	55°C	kW	1.57	1.57	1.57
		2°C	35°C		0.94	1.20	1.54
		35°C	18°C		1.20	1.56	2.14
	Cooling	35°C	7°C		1.96	2.59	3.46
		7°C	35°C		4.90	4.90	4.65
		7°C	55°C		3.50	3.50	3.50
COP	Heating	2°C	35°C	W/W	3.52	3.51	3.50
		35°C	18°C		4.60	4.50	4.20
EER	Cooling	35°C	7°C	W/W	4.60	4.50	4.20
		35°C	18°C		2.80	2.70	2.60

### Product Specification (Outdoor Unit)

Technical Specification		Unit	HU051MR U44	HU071MR U44	HU091MR U44
Operation Range (Leaving Water)	Heating	Min - Max °CDB	-25 ~ 35		
	Cooling		5 ~ 48		
Compressor	Quantity	EA	1		
	Type	-	Hermetic Sealed Scroll		
Refrigerant	Type	-	R32		
	GWP(Global Warming Potential)	-	675		
	Precharged Amount	g	1,500		
	t-CO <sub>2</sub> eq	-	1.013		
Piping connections	Outer Diameter	Gas	mm (inch)		
		Liquid	mm (inch)		
	Length	Standard	m		
		Max	m		
	Level Difference	Standard	m		
		Max	m		
	Chargeless-Pipe Length	m	10		
	Additional Charging Volume	g/m	30		
Rated Water Flow Rate (at LWT 35°C)	l/min	15.81	20.12	25.87	
Sound Power Level	Heating	Rated	dB(A)		
Sound Pressure Level (at 1m)	Heating	Rated	dB(A)		
		W x H x D	mm		
Dimensions	Unit	kg	950 x 834 x 330		
	Unit	kg	60.0		
Power Supply	Voltage, Phase, Frequency		V, Ø, Hz		
	Maximum Running Current	A	14.2	15.7	23.0
	Recommended Circuit Breaker	A	16	20	25
Wiring Connections	Power Supply Cable (Included Earth, H07RN-F)	mm <sup>2</sup> x cores	4.0 x 3		

#### Note

1. Due to our policy of innovation some specifications may be changed without notification.
2. Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.
3. Sound pressure level is measured on the rated condition in the anechoic rooms by ISO 3745 standard. Sound power level is measured on the rated condition in the reverberation rooms by ISO 3741 standard. Therefore, these values can be increased owing to ambient conditions during operation.
4. Performances are based on the following conditions (It is according to EN14511):
  - Interconnected Pipe Length is standard length and difference of Elevation (Outdoor - Indoor Unit) is 0m.
5. This product contains Fluorinated greenhouse gases.

### Product Specification (Indoor Unit)

Technical Specification		Unit	HN0916M NK4
Operation Range (Leaving Water)	Heating	Min - Max °CDB	15 ~ 65
	Cooling		5 ~ 27 (16 ~ 27) <sup>2)</sup>
Flow Sensor	DHW <sup>1)</sup>	-	15 ~ 80
	Type	-	Vortex
	Measuring Range	Min - Max	l/min
Piping Connections	Water Circuit	Min	l/min
		Flow (Trigger Point)	7
	Refrigerant Circuit	Inlet	mm (inch)
Outlet		mm (inch)	Male PT 25.4 (1)
Gas		mm (inch)	Ø15.88 (5/8)
Sound Power Level	Heating	Rated	dB(A)
		Rated	44
Dimensions	Unit	W x H x D	mm
Weight	Unit	kg	40.5
Electrical Specification		Unit	HN0916M NK4
Wiring Connections	Power and Communication Cable (Included Earth, H07RN-F)		mm <sup>2</sup> x cores
	Type	-	0.75 x 4 Sheath
Back up Heater	Number of Heating Coil		EA
	Capacity Combination		kW
	Operation		-
	Heating Steps		Step
	Power Supply		V, Ø, Hz
	Rated Current		A
	Maximum Current		A
	Power Supply Cable (Included Earth, H07RN-F)		mm <sup>2</sup> x cores

- 1) DHW 58 ~ 80°C Operating is available only when the booster heater is operating.
- 2) When fan coil unit not used.



**THERMA V™ R32 SPLIT HYDRO BOX TYPE**  
**PRODUCT SPECIFICATION**

**Drawings**


Category	Unit	Model Name		
		Capacity (kW)		
		5.5	7.0	9.0
1 Phase Model 220 - 240V, 1Ø, 50Hz	Outdoor Unit	HU051MR U44	HU071MR U44	HU091MR U44
	Indoor Unit	HN0916M NK4		

HU051MR U44 / HU071MR U44 / HU091MR U44

[Unit : mm]




No.	Part Name	Description
1	Air Outlet	-
2	Power and Communication Cable Hole	-
3	Gas Pipe Connection	Flare joint
4	Liquid Pipe Connection	Flare joint
5	Handle	-
6	Pipe Routing Hole (Front)	-
7	Pipe Routing Hole (Side)	-
8	Pipe Routing Hole (Back)	-





**Piping Connection Port**

[Unit : mm]



No.	Part Name	Description
1	Leaving Water Pipe	Male PT 1 inch
2	Entering Water Pipe	Male PT 1 inch
3	Refrigerant Pipe	Ø9.52 (mm)
4	Refrigerant Pipe	Ø15.88 (mm)
5	Water Pump	GROUNDFOS UPM3K 20-75 CHBL
6	Safety Valve	Open at water pressure 3bar
7	Control Box	PCB and terminal blocks
8	Thermal Switch	Cut-off power input to electric heater at 90°C (Manual return at 55°C)
9	Flow Sensor	SIKA VVX20 5-80LPM
10	Plate Heat Exchanger	Heat exchange between refrigerant and water
11	Pressure Gage	Indicates circulating water pressure
12	Expansion Tank	Absorbing volume change of heated water
13	Air Vent	Air purging when charging water
14	Electric Heater	6kW
15	Strainer	Filtering and stacking particles inside circulating water
16	Shut-off Valve	To drain or to block water, when pipe connecting

# THERMA V™ SPLIT HYDRO BOX TYPE



## Excellent Performance & Efficiency

- Twin rotary compressor
- R410A refrigerant
- Wide operation range (up to 57°C)
- Gold fin
- Solar thermal
- Energy state

## User Convenience

- Intuitive interface
- LG ThinQ
- 2nd circuit
- Various control options
- 3rd party boiler
- Energy monitoring
- Seasonal auto mode
- Low noise mode


## Easy Installation & Maintenance

- LG heating configurator
- Clip connection
- Flexible piping design

\* Detailed description for each function is presented on page 22 - 37.



## Energy Labeling



\* 14kW 10 model.  
\* A+++ to D scale.

## Split Hydro Box Concept

Split is a hydro box type which is that the indoor unit and outdoor unit are separated. Between two units are connected by refrigerant piping only, thus hydronic components such as plate heat exchanger, expansion tank and water pump are located inside of the indoor unit. For that reason, it is easy to withstand freezing issues regardless of outside ambient temperature.




## Capacity Range (Heating & Cooling)

### Split Hydro Box Type

Capacity Range [kW]	6	8	10	11	12	13	14	15	16	17
Heating Capacity					●		●		●	
Cooling Capacity			●		●	●				


## Operation Range (Heating & Cooling)



# PRODUCT FEATURES

## High Energy Efficiency


The energy label directive is a key factor of selecting heating device in Europe heating market. THERMA V Split type has an energy label rating over A+++ in ErP energy labeling regulation.



\* Test Condition  
Test procedure follows EN14825 (Low temp average), Based on the single phase model line up.

## Energy Efficiency at -2°C

Energy efficiency is higher than others. (Condition : Ambient temp -2°C / Leaving water temp 55°C)




\* Peak value / Split models

## BLDC (Brushless Direct Current Motor) Compressor


THERMA V is equipped with a BLDC compressor that uses a strong neodymium magnet. The compressor has improved efficiency compared to standard AC inverter product and it is optimized for seasonal efficiency.

- Minimized oil circulation
- High efficiency motor
- Optimized compression
- Optimized vibration, noise
- High reliability



## Corrosion Resistant Heat Exchanger

Outdoor heat exchanger is coated with a gold-colored anti-corrosive epoxy treatment on the aluminum coil, to prevent corrosion. This exhibits pre-eminent heat transfer properties of the coil for a lengthy period, whereas non-Gold Fin™ coils progressively lose efficiency due to surface corrosion. Gold Fin™ fin is extremely suitable for areas affected by high pollution and areas exposed to salt water breeze.



• Gold Fin™ is long lasting, durable and makes the outdoor unit look prestigious.

# PRODUCT SPECIFICATION

## Split Hydro Box Type

### IDU

HN1616 NK3  
HN1639 NK3

### ODU

HU121 U33  
HU141 U33  
HU161 U33  
HU123 U33  
HU143 U33  
HU163 U33



### Features

- High energy efficiency
- Maximum 57°C LWT
- Intuitive interface
- LG ThinQ
- Corrosion resistant heat exchanger (Gold Fin)
- KEYMARK / EHPA certification / MCS / Eurovent certification

Note  
1. Approved model by EHPA : HU123 U33, HU143 U33, HU163 U33.

### Model Line up

Category	Unit	Model Name		
		Capacity (kW)		
		12.0	14.0	16.0
1 Phase Model 220 ~ 240V, 1Ø, 50Hz	Outdoor Unit	HU121 U33	HU141 U33	HU161 U33
	Indoor Unit	HN1616 NK3		
3 Phase Model 380 ~ 415V, 3Ø, 50Hz	Outdoor Unit	HU123 U33	HU143 U33	HU163 U33
	Indoor Unit	HN1639 NK3		

### Seasonal Energy

Description		Outdoor Unit	HU121 U33	HU141 U33	HU161 U33	
		Indoor Unit	HN1616 NK3			
Space Heating (According to EN14825)	Average Climate Water Outlet 35°C	SCOP	W/W	4.45	4.45	4.3
		Rated Heat Output (P <sub>rated</sub> )	kW	9	10	10
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	175	175	169
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A+++	A+++	A++
		Annual Energy Consumption	kWh	4,177	4,408	4,802
	Average Climate Water Outlet 55°C	SCOP	-	3.32	3.32	3.32
		Rated Heat Output (P <sub>rated</sub> )	kW	10	10	10
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	130	130	130
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A++	A++	A++
		Annual Energy Consumption	kWh	6,154	6,154	6,154

Description		Outdoor Unit	HU123 U33	HU143 U33	HU163 U33	
		Indoor Unit	HN1639 NK3			
Space Heating (According to EN14825)	Average Climate Water Outlet 35°C	SCOP	W/W	4.45	4.45	4.3
		Rated Heat Output (P <sub>rated</sub> )	kW	9	10	10
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	175	175	169
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A+++	A+++	A++
		Annual Energy Consumption	kWh	4,179	4,410	4,804
	Average Climate Water Outlet 55°C	SCOP	-	3.32	3.32	3.32
		Rated Heat Output (P <sub>rated</sub> )	kW	10	10	10
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	130	130	130
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A++	A++	A++
		Annual Energy Consumption	kWh	6,156	6,156	6,156

### Nominal Capacity and Nominal Input

Description		OAT (DB)	LWT (DB)	Outdoor Unit	HU121 U33	HU141 U33	HU161 U33
					HU123 U33	HU143 U33	HU163 U33
					HN1616 NK3		
					HN1639 NK3		
Nominal Capacity	Heating	7°C	35°C	kW	12.00	14.00	16.00
		7°C	55°C		12.50	12.50	12.50
		2°C	35°C		10.33	10.83	11.95
	Cooling	35°C	18°C		10.40	12.00	13.00
		35°C	7°C		7.94	8.50	8.92
		7°C	35°C		2.64	3.18	3.76
Nominal Power Input	Heating	7°C	55°C	kW	4.94	4.94	4.94
		2°C	35°C		2.93	3.09	3.41
		35°C	18°C		2.60	3.08	3.60
	Cooling	35°C	7°C		2.66	3.03	3.30
		7°C	35°C		4.55	4.41	4.26
		7°C	55°C		2.53	2.53	2.53
COP	Heating	2°C	35°C	W/W	3.53	3.50	3.50
		35°C	18°C		4.00	3.90	3.61
EER	Cooling	35°C	7°C	W/W	2.98	2.81	2.70
		35°C	18°C				

# PRODUCT SPECIFICATION

## Split Hydro Box Type

### Product Specification (Outdoor Unit)

Description			Unit	HU121 U33	HU141 U33	HU161 U33	HU123 U33	HU143 U33	HU163 U33
Operation Range (Leaving Water)	Heating	Min - Max	°CDB	-20 - 35					
	Cooling		°C	5 - 48					
Compressor	Quantity		EA	1					
	Type		-	Hermetic Sealed Twin Rotary					
Refrigerant	Type		-	R410A					
	GWP (Global Warming Potential)		-	2,087.5					
	Precharged Amount		g	2,300					
	t-CO <sub>2</sub> eq		-	4.801					
Piping Connections	Outer Diameter	Gas	mm (inch)	Ø15.88 (5/8)					
		Liquid	mm (inch)	Ø9.52 (3/8)					
	Length	Standard	m	7.5					
		Max	m	50					
	Level Difference	Max	m	30					
	Chargeless-Pipe Length		m	7.5					
Additional Charging Volume		g/m	40						
Rated Water Flow Rate (at LWT 35°C)			l/min	34.0	40.0	46.0	34.0	40.0	46.0
Sound Power Level	Heating	Rated	dB(A)	66					
Sound Pressure Level (at 1m)	Heating	Rated	dB(A)	58					
Dimensions	Unit	W x H x D	mm	950 x 1,380 x 330					
Weight	Unit		kg	94.0					
Power Supply	Voltage, Phase, Frequency		V, Ø, Hz	220 - 240, 1, 50			380 - 415, 3, 50		
	Maximum Running Current		A	25.0			16.1		
	Recommended Circuit Breaker		A	40			20		
Wiring Connections	Power Supply Cable (Included Earth, H07RN-F)		mm <sup>2</sup> x cores	6.0 x 3			2.5 x 5		

**Note**

1. Due to our policy of innovation some specifications may be changed without notification.
2. Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.
3. Sound power level is measured on the rated condition in the reverberation rooms by ISO 3741 standard. Therefore, these values can be increased owing to ambient conditions during operation.
4. Performances are based on the following conditions (It is according to EN14511):
  - Interconnected Pipe Length is standard length and difference of Elevation (Outdoor - Indoor Unit) is 0m.
5. This product contains Fluorinated greenhouse gases.

### Product Specification (Indoor Unit)

Technical Specification			Unit	HN1616 NK3	HN1639 NK3
Operation Range (Leaving Water)	Heating	Min - Max	°CDB	15 - 57	
	Cooling			5 - 27 (16 - 27) <sup>2)</sup>	
	DHW <sup>1)</sup>			15 - 80	
Piping Connections	Water Circuit	Inlet	mm (inch)	Male PT 25.4 (1)	
		Outlet	mm (inch)	Male PT 25.4 (1)	
	Refrigerant Circuit	Gas	mm (inch)	Ø15.88 (5/8)	
		Liquid	mm (inch)	Ø9.52 (3/8)	
Sound Power Level	Heating	Rated	dB(A)	44	
Dimensions	Unit	W x H x D	mm	490 x 850 x 315	
Weight	Unit		kg	42.2	45.0
Electrical Specification			Unit	HN1616.NK3	HN1639.NK3
Wiring Connections	Power and Communication Cable (Included Earth, H07RN-F)		mm <sup>2</sup> x cores	0.75 x 4	
Back up Heater	Type		-	Sheath	Sheath
	Number of Heating Coil		EA	2	3
	Capacity Combination		kW	3.0 + 3.0	3.0 + 3.0 + 3.0
	Operation		-	Automatic	Automatic
	Heating Steps		Step	2	2
	Power Supply		V, Ø, Hz	220 - 240, 1, 50	220 - 240, 1, 50
	Rated Current		A	25.0	13.0
	Maximum Current		A	32.0	16.3
	Power Supply Cable (Included Earth, H07RN-F)		mm <sup>2</sup> x cores	4.0 x 3	2.5 x 4

- 1) DHW 58 - 80°C Operating is available only when the booster heater is operating.
- 2) When fan coil unit not used.




# PRODUCT SPECIFICATION

## Drawings

Category	Unit	Model Name		
		Capacity (kW)		
		12.0	14.0	16.0
1 Phase Model 220 - 240V, 1Ø, 50Hz	Outdoor Unit	HU121 U33	HU141 U33	HU161 U33
	Indoor Unit		HN1616 NK3	
3 Phase Model 380 - 415V, 3Ø, 50Hz	Outdoor Unit	HU123 U33	HU143 U33	HU163 U33
	Indoor Unit		HN1639 NK3	

HU121 U33 / HU141 U33 / HU161 U33 / HU123 U33 / HU143 U33 / HU163 U33


[Unit : mm]



HN1616 NK3 / HN1639 NK3


[Unit : mm]

External





No.	Part Name	Description
1	Control Panel	Built-in remote controller


Internal




No.	Part Name	Description
1	Leaving Water Pipe	Male PT 1 inch
2	Entering Water pipe	Male PT 1 inch
3	Refrigerant Pipe	Ø9.52 (mm)
4	Refrigerant Pipe	Ø15.88 (mm)
5	Water Pump	Max head 9.5 / 7 / 6m
6	Safety Valve	Open at water pressure 3bar
7	Control Box	PCB and terminal blocks
8	Thermal Switch	Cut-off power input to electric heater at 90°C (Manual return at 55°C)
9	Flow Switch	Minimum operation range at 15LPM
10	Plate Heat Exchanger	Heat exchange between refrigerant and water
11	Pressure Gage	Indicates circulating water pressure
12	Expansion Tank	Absorbing volume change of heated water
13	Air Vent	Air purging when charging water
14	Electric Heater	Please refer to the below Page 'Model name and related information'
15	Strainer	Filtering and stacking particles inside circulating water
16	Shut-Off Valve	To drain or to block water, when pipe connecting




## Excellent Performance & Efficiency



## User Convenience




## Easy Installation & Maintenance



\* Detailed description for each function is presented on page 22 - 37.




## Energy Labeling



\* 16kW 10 model.  
\* A+++ to D scale.

## Split DHW Tank Integrated Concept

IWT (Integrated Water Tank) is an integrated unit that indoor unit is combined with a domestic hot water tank while outdoor unit is separately located outside. THERMA V IWT is more suitable for the house which has less indoor spaces because hydronic components such as DHW tank and buffer tank normally installed additionally are integrated as one unit.



## Key Components


No.	Part Name	No.	Part Name
1	Heating / Cooling Inlet	A	Buffer Tank
2	Heating / Cooling Outlet	B	Circulating Pump
3	Warm Sanitary	C	Electric Flow Heater
4	DHW - Circulation	D	TT3000 Controller
5	Cold Sanitary Water - Supply	E	Condenser
6	Gas Pipe 5/8" - Refrigerant	F	3Way Valve
7	Liquid Pipe 3/8" - Refrigerant	G	DHW Tank
8	Mg. Anode		
9	Wiring Connection		

## Capacity Range (Heating & Cooling)

### Split DHW Tank Integrated Type

Capacity Range [kW]	5	6	7	8	9	10	11	12	13	14	15	16	17
Heating Capacity					●			●		●		●	
Cooling Capacity					●	●	●	●					

## Operation Range (Heating & Cooling)



# PRODUCT FEATURES

## Save Space & Time

Compared with conventional system, easy & quick installation is possible and smaller spaces are required for installation.

Conventional	New (DHW Tank Integrated Type)
<ul style="list-style-type: none"> <li>Buffer Tank</li> <li>AWHP Indoor Unit</li> <li>Water Tank</li> <li>Water Pipe</li> </ul>	<ul style="list-style-type: none"> <li><b>All in One</b> Small space for product installation 200 liter DHW tank with extra 40 liter.</li> <li><b>Less Water Piping Work</b> More easy &amp; Save time.</li> </ul>

- Enough rooms for product installation.
- Need to secure the space for water tank.
- More water piping work & More installation time.


## Sophisticated and Harmonious Exterior

THERMA V Split IWT indoor unit is suitable to install in indoor space like utility room, kitchen, etc. thanks to the sophisticated & harmonious exterior with white color and modern design.



## Space Heating Efficiency

The energy label directive is a key factor of selecting heating device in Europe heating market. THERMA V split DHW tank integrated type has an energy label rating A++ in ErP energy labeling regulation.




## Quiet Operation

Due to quiet operation, it creates an atmosphere of calm and restfulness in case of indoor installation.

### Operation Noise

- Sound power level : 36dB(A)
- Sound pressure level : 27dB(A)

Quiet operation.  
Calm and restfulness indoor environment.



## Temperature + Pressure Control & Quick Operating Response

Pressure control secures faster and more exact response than temperature control, so it reduces the time to reach the target water temperature by 44%.

Faster and More Exact with Pressure Control	Quick Reaching to Target Temperature
<ul style="list-style-type: none"> <li>• Quick response due to sensing with ready for operation.</li> <li>• Ensures to reach target performance point without failing to keep a reliable operation.</li> </ul>	<ul style="list-style-type: none"> <li>• Pressure control takes up to 44% less time to reach the desired water temperature with a high level of accuracy and stability.</li> </ul>

\* Based on internal test data.

# PRODUCT SPECIFICATION

## Split DHW Tank Integrated Type

### IDU

HN1616T NBO

### ODU

HU091 U43

HU121 U33

HU141 U33

HU161 U33

HU123 U33

HU143 U33

HU163 U33

Mandatory accessory : PP485B00K.ENCXLEU



EHPA for Austria, Switzerland and Germany

**R410A**

**58°C**

**A++**

### Features

- Space (Floor) heating efficiency with ErP A++<sup>1)</sup> class
- Maximum 58°C LWT
- Corrosion resistant heat exchanger (Gold Fin)
- EHPA certification

1) under average climate conditions for medium-temperature application  
2) Approved model by EHPA : HU091 U43, HU123 U33, HU143 U33, HU163 U33.

### Model Line up

Category	Unit	Model Name Capacity (kW)			
		9.0	12.0	14.0	16.0
1 Phase Model 220 - 240V, 1Ø, 50Hz	Outdoor Unit	HU091 U43	HU121 U33	HU141 U33	HU161 U33
	Indoor Unit	HN1616T NBO			
3 Phase Model 380 - 415V, 3Ø, 50Hz	Outdoor Unit	-	HU123 U33	HU143 U33	HU163 U33
	Indoor Unit	-	HN1616T NBO		

Note  
1. PP485B00K. ENCXLEU is required for communication between outdoor unit and indoor unit. (Install at outdoor unit)

### Seasonal Energy

Description		Outdoor Unit	HU091 U43	HU121 U33	HU141 U33	HU161 U33		
			Indoor Unit	HU123 U33	HU143 U33	HU163 U33		
Space Heating (According to EN14825)	Average Climate	Water Outlet 35°C	HN1616T NBO					
			SCOP	W/W	4.04	4.20	4.15	4.15
			Rated Heat Output (P <sub>rated</sub> )	kW	7	10	10	11
			Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	159	165	163	163
			Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A++	A++	A++	A++
	Average Climate	Water Outlet 55°C	Annual Energy Consumption	kWh	3,321	4,820	5,183	5,376
			SCOP	-	2.88	3.00	3.00	3.00
			Rated Heat Output (P <sub>rated</sub> )	kW	6	10	10	10
			Seasonal Space Heating Efficiency (η <sub>s</sub> )	%	112	117	117	117
			Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A+	A+	A+	A+
Domestic Hot Water Heating	Average Climate	Annual Energy Consumption	kWh	4,020	6,755	6,755	6,755	
		Declared Load Profile	-	XL	XL	XL	XL	
		Water Heating Efficiency (η <sub>wh</sub> )	%	98	89	89	89	
		Water Heating Energy Eff. Class (A + to F Scale)	-	A	A	A	A	
			Annual Energy Consumption	kWh	1,710	1,881	1,881	1,881

### Nominal Capacity and Nominal Input

Description	OAT (DB)	LWT (DB)	Outdoor Unit	Indoor Unit	HU091 U43	HU121 U33	HU141 U33	HU161 U33
					HU123 U33	HU143 U33	HU163 U33	
Nominal Capacity	Heating	7°C	35°C	kW	9.00	12.00	14.00	16.00
		7°C	55°C		6.70	12.50	12.50	12.50
		2°C	35°C		7.30	9.81	10.37	11.45
	Cooling	35°C	18°C		9.00	10.40	11.00	12.00
		35°C	7°C		6.43	6.75	7.14	7.79
		7°C	35°C		2.23	2.78	3.43	4.18
Nominal Power Input	Heating	7°C	55°C	kW	2.79	4.89	4.89	4.89
		2°C	35°C		2.27	3.12	3.30	3.64
		35°C	18°C		2.88	3.30	3.53	4.00
	Cooling	35°C	7°C		2.76	3.20	3.42	3.87
		7°C	35°C		4.04	4.32	4.08	3.83
		7°C	55°C		2.40	2.56	2.56	2.56
COP	Heating	2°C	35°C	W/W	3.22	3.14	3.14	3.15
		35°C	18°C		3.12	3.15	3.12	3.00
EER	Cooling	35°C	7°C	W/W	2.33	2.11	2.09	2.01
		35°C	7°C		2.33	2.11	2.09	2.01

### Product Specification (Outdoor Unit)

Description	Unit	HU091 U43	HU121 U33	HU141 U33	HU161 U33	HU123 U33	HU143 U33	HU163 U33
Operation Range (Leaving Water)	Heating	°CDB -20 ~ 35						
	Cooling	°CDB 5 ~ 48						
Compressor	Quantity	EA 1						
	Type	- Hermetic Sealed Twin Rotary						
Refrigerant	Type	- R410A						
	GWP(Global Warming Potential)	- 2,087.5						
	Precharged Amount <sup>1)</sup>	g	1,800					2,300
	t-CO <sub>2</sub> eq	-	3.758					4.801
Piping Connections	Outer Diameter	Gas	mm (inch) Ø15.88 (5/8)					
		Liquid	mm (inch) Ø9.52 (3/8)					
	Length	Standard	m 7.5					
		Max	m 50					
	Level Difference	Max	m 30					
	Chargeless-Pipe Length		m 7.5					
Additional Charging Volume	g/m	40						
Rated Water Flow Rate (at LWT 35°C)	l/min	26.0	34.0	40.0	46.0	34.0	40.0	46.0
Sound Power Level	Heating	dB(A) 65						
	Rated	dB(A) 58						
Sound Pressure Level (at 1m)	Heating	dB(A) 57						
	Rated	dB(A) 58						
Dimensions	Heating	mm 950x834x330						
	Rated	mm 950 x 1,380 x 330						
Weight	Unit	kg 59.0						
	WxHxD	kg 94.0						
Power Supply	Voltage, Phase, Frequency	V, Ø, Hz 220 - 240, 1, 50						
	Maximum Running Current	A	19.0				25.0	16.1
	Recommended Circuit Breaker	A	30				40	20
Wiring Connections	Power Supply Cable (Included Earth, H07RN-F)	mm <sup>2</sup> x cores	4.0 x 3				6.0 x 3	2.5 x 5

1) After installation, additional refrigerant must be charged 800g for HU091 U43 and 1,200g for the others.

#### Note

1. Due to our policy of innovation some specifications may be changed without notification.
2. Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.
3. Sound power level is measured on the rated condition in the reverberation rooms by ISO 3741 standard. Therefore, these values can be increased owing to ambient conditions during operation.
4. Performances are based on the following conditions (It is according to EN14511):
  - Interconnected Pipe Length is standard length and difference of Elevation (Outdoor - Indoor Unit) is 0m.
5. This product contains Fluorinated greenhouse gases.

# PRODUCT SPECIFICATION

## Product Specification (Indoor Unit)

Description			Unit	HN1616T NBO	
Operation Range (Leaving Water)	Heating	Min - Max	°CDB	25 - 58	
	Cooling		°CDB	7 - 25	
	DHW		°CDB	10 - 60	
DHW Tank	Type		-	Hydro module with integrated boiler	
	Material		-	Enameled steel	
	Water Volume	Rated	ℓ	200	
	Internal Thermal Protect limit		°C	95	
	Maximum Water Pressure Limit		bar	10	
	Insulation	Material		-	Polyurethane foam
		Thickness		mm	50
Heat loss (for 24hr)			kWh	1.67	
Buffer Tank	Water Volume	Rated	ℓ	40	
	Material		-	Steel powder coated	
	Insulation Material		-	Closed cell foamed rubber	
Piping Connections	Water Circuit	Inlet	mm (inch)	Male PT 25.4 (1)	
		Outlet	mm (inch)	Male PT 25.4 (1)	
	DHW Tank Water Circuit	Cold Inlet	mm (inch)	Male PT 19.05 (3/4)	
		Hot Outlet	mm (inch)	Male PT 25.4 (1)	
	Refrigerant Circuit	Recirculation	mm (inch)	Male PT 19.05 (3/4)	
		Gas	mm (inch)	Ø15.88 (5/8)	
	Liquid	mm (inch)	Ø9.52 (3/8)		
Sound Power Level	Heating	Rated	dB(A)	36	
Sound Pressure Level (at 1m)	Heating	Rated	dB(A)	27	
Dimensions	Unit	W x H x D	mm	607 x 2,079 x 725	
Weight	Unit		kg	228	
Electrical Specification			Unit	HN1616T NBO	
Back up Heater (1) (1 phase)	Type		-	Sheath	
	Number of Heating Coil		EA	1	
	Capacity Combination		kW	2	
	Operation		-	Automatic	
	Heating Steps		Step	1	
	Power Supply		V, Ø, Hz	230, 1, 50	
	Rated Current		A	8.7	
	Maximum Current		A	11.1	
Wiring Connections	Power Supply Cable (Included Earth, H07RN-F)		mm <sup>2</sup> x cores	4.0 x 3	
Back up Heater (2) (1 phase)	Type		-	Sheath	
	Number of Heating Coil		EA	2	
	Capacity Combination		kW	2.0 + 2.0	
	Operation		-	Automatic	
	Heating Steps		Step	1	
	Power Supply		V, Ø, Hz	230, 1, 50	
	Rated Current		A	17.4	
	Maximum Current		A	19.9	
Wiring Connections	Power Supply Cable (Included Earth, H07RN-F)		mm <sup>2</sup> x cores	4.0 x 3	
Back up Heater (3) (3 phase)	Type		-	Sheath	
	Number of Heating Coil		EA	3	
	Capacity Combination		kW	2.0 + 2.0 + 2.0	
	Operation		-	Automatic	
	Heating Steps		Step	1	
	Power Supply		V, Ø, Hz	400, 3, 50	
	Rated Current		A	8.7	
	Maximum Current		A	11.1	
Wiring Connections	Power Supply Cable (Included Earth, H07RN-F)		mm <sup>2</sup> x cores	2.5 x 5	


- Note
- Due to our policy of innovation some specifications may be changed without notification.
  - Wiring cable size must comply with the applicable local and national code. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.
  - Sound pressure level is measured on the rated condition in the anechoic rooms by ISO 3745 standard. Sound power level is measured on the rated condition in the reverberation rooms by ISO 3741 standard. Therefore, these values can be increased owing to ambient conditions during operation.
  - This is true for pipe connections of suitable dimensions and joint distance of up to 20m. Pipe dimensions and types of pumps must always be verified or determined by the designing engineer of electrical installations. Circulation pumps must be dimensioned in such a way so as to ensure rated voltage (see table) through the device.
  - The guideline about cable is taken into account laying B2 from the table A.52.4 - IEC 60364-5-52. The cable in the installation pipe is fixed to the wall.
  - The size of Electrical Heater and the Fuses depend on the choice of the connection power.
  - Joint maximal load (circulation pumps, electronic valves ...) which can be connected to or powered by the internal unit, must not exceed the specified value. Higher consumed parts (i.e. pumps) should have their own supply.
  - This product contains Fluorinated greenhouse gases.

## Drawings


Category	Unit	Model Name			
		Capacity (kW)			
		9.0	12.0	14.0	16.0
1 Phase Model 220 - 240V, 1Ø, 50Hz	Outdoor Unit	HU091 U43	HU121 U33	HU141 U33	HU161 U33
	Indoor Unit	HN1616T NBO			
3 Phase Model 380 - 415V, 3Ø, 50Hz	Outdoor Unit	-	HU123 U33	HU143 U33	HU163 U33
	Indoor Unit	HN1616T NBO			

HU091 U43

[Unit : mm]



No.	Part Name	Description
1	Air Outlet	-
2	Power and Communication Cable Hole	-
3	Gas Pipe Connection	Flare joint
4	Liquid Pipe Connection	Flare joint
5	Handle	-
6	Pipe Routing Hole (Front)	-
7	Pipe Routing Hole (Side)	-
8	Pipe Routing Hole (Back)	-






Piping Connection Port

# PRODUCT SPECIFICATION

HU121 U33 / HU141 U33 / HU161 U33 / HU123 U33 / HU143 U33 / HU163 U33

[Unit : mm]





Piping Connection Port



No.	Part Name	Description
1	Air Outlet	-
2	Power and Communication Cable Hole	-
3	Gas Pipe Connection	Flare joint
4	Liquid Pipe Connection	Flare joint
5	Handle	-
6	Pipe Routing Hole (Front)	-
7	Pipe Routing Hole (Side)	-
8	Pipe Routing Hole (Back)	-

HN1616T NB0

[Unit : mm]





DETAILA  
SCALE 1 : 5




No.	Part Name	No.	Part Name
1	Heating / Cooling Inlet	A	Buffer Tank
2	Heating / Cooling Outlet	B	Circulating Pump
3	Warm Sanitary	C	Electric Flow Heater
4	DHW - Circulation	D	TT3000 Controller
5	Cold Sanitary Water - Supply	E	Condenser
6	Gas Pipe 5/8" - Refrigerant	F	3Way Valve
7	Liquid Pipe 3/8" - Refrigerant	G	DHW Tank
8	Mg. Anode	H	Flow Switch
9	Wiring Connection	I	Ball Valve
10	Safety Valve, Pressure Gauge, Air Vent	J	Safety Thermostat
		K	Wiring Connection

# THERMA V™ SPLIT HIGH TEMPERATURE



## Excellent Performance & Efficiency



## User Convenience




## Easy Installation & Maintenance



\* Detailed description for each function is presented on page 22 - 37.




## Energy Labeling




\* 16kW 1Ø model.  
\* A+++ to D scale.

## THERMA V High Temperature Cycle



## High Temperature Concept

THERMA V high temperature is a kind of split type that consists of an indoor unit and an outdoor unit. Thanks to the cascade 2 stage compression technology, it can supply such high leaving water temperature - 80°C with high energy efficiency.




## Capacity Range (Heating)

### High Temperature Model

Capacity Range [kW]	5	6	7	8	9	10	11	12	13	14	15	16	17
Heating Capacity												●	


## Operation Range (Heating & Cooling)



# PRODUCT FEATURES

## Cascade 2 Stage Compression Technology

THERMA V high temp can produce Max 80°C hot water with high efficiency through cascade 2 stage compression (R410A to R134a) technology in order to replace simply an existing old boiler heating system which demands hot water supply.




\* Condition for HT model : Outdoor air temp 18°C, Entering water temp 70°C  
 \* Condition for LT model : Outdoor air temp 18°C, Entering water temp 55°C

Note  
 1. OAT : Outdoor Air Temperature, EWT : Entering Water Temperature, LWT : Leaving Water Temperature.


## High Energy Efficiency

By applying efficient compressor and optimally designed structure, the more energy saving, the lower operating cost make sooner return on initial investment.




## Excellent Performance at LAT

New H/T Split provides excellent heating performance – especially at low ambient temperature. Even at outside temperatures of -7°C and LWT of 80°C, New H/T Split is able to provide 16kW heating capacity improved by 16.8% compared to the previous models.




## Low Noise Level

Through cutting edge technology for DC inverter compressor, operating noise level of indoor & outdoor unit has been reduced and serves more comfort.



## Quick Defrosting

Through R134a compressor controlling technology, necessary time for defrost operation has been minimized effectively. (LG Patent)





# PRODUCT FEATURES


## Suitable for Old Radiator

THERMA V high temperature is suitable for houses which have poor insulation or existing old radiator, or have to meet sanitary water regulation which needs high water temperature.




## Light Weight

Lighter weight enables easy installation work.



## Low Current Level

LG high temperature THERMA V can be easily installed without any incurring any additional costs to the electric connections.



# THERMA V™ SPLIT HIGH TEMPERATURE PRODUCT SPECIFICATION

## Split High Temperature

IDU  
HN1610H NK3  
ODU  
HU161HA U33



### Features

- Higher energy efficiency
- Cascade 2 stage compression
- Maximum 80°C LWT
- Suitable for old radiator
- Only for heating (No cooling)
- Quick defrosting
- Efficient & Flexible design
- KEYMARK / MCS / Eurovent certification

### Model Line up

Category	Unit	Model Name
		Capacity (kW)
1 Phase Model 220 – 240V, 1Ø, 50Hz	Outdoor Unit	HU161HA U33
	Indoor Unit	HN1610H NK3

### Seasonal Energy

Description		Outdoor Unit	HU161HA U33
		Indoor Unit	HN1610H NK3
Space Heating (According to EN14825)	Average Climate Water Outlet 35°C	SCOP	3.23
		Rated Heat Output (P <sub>rated</sub> )	13
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	126
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	A+
	Average Climate Water Outlet 55°C	Annual Energy Consumption	8,618
		SCOP	3.01
		Rated Heat Output (P <sub>rated</sub> )	11
		Seasonal Space Heating Efficiency (η <sub>s</sub> )	117
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	A+
		Annual Energy Consumption	7,424

### Nominal Capacity and Nominal Input

Description	OAT (DB)	LWT (DB)	Outdoor Unit	HU161HA U33
			Indoor Unit	HN1610H NK3
Nominal Capacity	Heating	7°C	kW	16.00
		7°C		14.00
		2°C		16.00
Nominal Power Input	Heating	7°C	kW	4.89
		7°C		5.00
		2°C		4.92
COP	Heating	7°C	W/W	3.27
		7°C		2.78
		2°C		3.25

### Product Specification (Outdoor Unit)

Description			Unit	HU161HA U33
Operation Range (Outdoor Temp)	Heating	Min – Max	°CDB	-25 – 35
	Quantity		EA	1
Compressor	Type		-	Hermetic Sealed Scroll
	Type		-	R410A
Refrigerant	GWP (Global Warming Potential)		-	2087.5
	Precharged Amount		g	3,800
	t-CO <sub>2</sub> eq		-	7.933
Piping Connections	Outer Diameter	Gas	mm (inch)	Ø15.88 (5/8)
		Liquid	mm (inch)	Ø9.52 (3/8)
	Length	Standard	m	7.5
		Max	m	50
	Level Difference	Max	m	30
	Chargeless-Pipe Length		m	7.5
	Additional Charging Volume		g/m	40
	Sound Power Level	Heating	Rated	dB(A)
Sound Pressure Level (at 1m)	Heating	Rated	-	55
Dimensions	Unit	W x H x D	mm	950 x 1,380 x 330
	Unit		kg	89.0
Power Supply	Voltage, Phase, Frequency		V, Ø, Hz	220 – 240, 1, 50
	Maximum Running Current		A	18.9
	Recommended Circuit Breaker		A	20
Wiring Connections	Power Cable (Included Earth)		mm <sup>2</sup> x cores	4.0 x 3 (H07RN-F)

### Product Specification (Indoor Unit)

Description			Unit	HN1610H NK3
Operation Range (Leaving Water)	Heating, DHW	Min – Max	°CDB	25 – 80
	Quantity		EA	1
Compressor	Type		-	Hermetic Sealed Twin Rotary
	Type		-	R134a
Refrigerant	GWP (Global Warming Potential)		-	1430.0
	Precharged Amount		g	1,800
	t-CO <sub>2</sub> eq		-	2.574
Heat Exchanger	Water Circuit	Type	-	Brazed Plate HEX
	Refrigerant Circuit	Type	-	Brazed Plate HEX
Piping Connections	Water Circuit	Inlet	mm (inch)	Male PT 25.4 (1)
		Outlet	mm (inch)	Male PT 25.4 (1)
	Refrigerant Circuit	Gas	mm (inch)	Ø15.88 (5/8)
		Liquid	mm (inch)	Ø9.52 (3/8)
Rated Water Flow Rate (at LWT 35°C)			ℓ/min	46
Sound Power Level	Heating	Rated	dB(A)	58 / 63 <sup>1)</sup>
Sound Pressure Level (at 1m)	Heating	Rated	dB(A)	50
Dimensions	Unit	W x H x D	mm	520 x 1,080 x 330
Weight	Unit		kg	84.0
Electrical Specification			Unit	HN1610H NK3
Power Supply	Voltage, Phase, Frequency		V, Ø, Hz	220 – 240, 1, 50
	Maximum Running Current		A	20.2
	Recommended Circuit Breaker		A	25
Wiring Connections	Power Cable (Included Earth)		mm <sup>2</sup> x cores	4.0 x 3 (H07RN-F)
	Communication Cable (Included Earth)		mm <sup>2</sup> x cores	1.0 – 1.5 x 2 (VCTF-SB)
Accessory Kit of the Indoor Unit			Unit	HN1610H NK3
Remote Controller			-	RS3
Water Tank Temperature	Sensor Size		Ø	7
Sensor with Holder	Resistance		kΩ	5
Strainer	Mesh Size / Material		-	28 mesh / Stainless Steel

1) This sound power level (63dB(A)) is when cooling fan is operated.

#### Note

- Due to our policy of innovation some specifications may be changed without notification.
- Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.
- Sound Level Values are measured at Noise Measuring chamber accordance with standard. Therefore, these values depend on the ambient conditions and values are normally higher in actual operation.
- Performances are based on the following conditions (It is according to EN14511):
  - Heating : Inlet/Outlet Water Temp 30°C / 35°C, Outdoor Temp 7°CDB / 6°CWB
  - Interconnected Pipe Length is 5m and difference of Elevation (Outdoor – Indoor Unit) is 0m.
- This product contains Fluorinated greenhouse gases.


# THERMA V™ SPLIT HIGH TEMPERATURE PRODUCT SPECIFICATION

## Drawings


Category	Unit	Model Name
		Capacity (kW)
1 Phase Model 220 - 240V, 1Ø, 50Hz	Outdoor Unit	HU161HA U33
	Indoor Unit	HN1610H NK3

HU161HA U33

[Unit : mm]




No.	Part Name	Description
1	Air Outlet	-
2	Power and Communication Cable Hole	-
3	Gas Pipe Connection	Flare joint
4	Liquid Pipe Connection	Flare joint
5	Handle	-
6	Pipe Routing Hole (Front)	-
7	Pipe Routing Hole (Side)	-
8	Pipe Routing Hole (Back)	-



Piping Connection Port

HN1610H NK3

[Unit : mm]



















No.	Part Name	Description
1	Refrigerant Pipe	Ø9.52 (mm)
2	Refrigerant Pipe	Ø15.88 (mm)
3	Leaving Water Pipe	Male PT 25mm (1 inch)
4	Entering Water Pipe	Male PT 25mm (1 inch)
5	Control Box	PCB and terminal blocks
6	Flow Switch	Minimum operation range at 15LPM
7	Plate Heat Cxchanger	Heat exchanger between refrigerant and water
8	Plate Heat Cxchanger	Heat exchanger between refrigerant and refrigerant
9	Compressor	EPT525MBA
10	Accumulator	716 cc



**THERMA V™**  
**ACCESSORIES**






## Accessories Provided by LG






Category	Model Name	Model Number	Figure	Relevant Function	Purpose	Feature
Sensors	Room Temperature Sensor	PQRSTA0		Room Temperature Based Control	To detect room air temperature for room temperature based control	• Max wire length : 15m
	2 <sup>nd</sup> Circuit Thermistor	PRSTAT5K10		2 <sup>nd</sup> Circuit	To detect 2 <sup>nd</sup> circuit temperature when using 2 <sup>nd</sup> circuit function	• 5kΩ thermistor, 10m
	Domestic Hot Water Sensor	PHRSTA0		Domestic Hot Water Heating	To detect DHW tank temperature	• Included in PHLTA kit
Valves	3Way Valve	OSHA-3V		Domestic Hot Water Heating	To divert water flow between space heating and DHW heating	• Size : DN 20 G 1" connection, male threaded
	Thermostatic Mixing Valve	OSHA-MV OSHA-MV1		Domestic Hot Water Supply	To blend hot water with cold water for ensuring constant, safe shower and bath outlet temperature, preventing scalding.	• Size : 3/4" DN20 male threaded • Size : 1" DN25 male threaded
Tanks	Domestic Hot Water Tank (Single Coil)	OSHW-200F OSHW-300F OSHW-500F		Domestic Hot Water Heating	To generate and store domestic hot water	• Storage volume : 200L, 300L, 500L • Type : Internal single coil • Material : Stainless steel • Capacity of booster heater : 2.4kW
	Domestic Hot Water Tank (Double Coil)	OSHW-300FD		Domestic Hot Water Heating	To generate and store domestic hot water	• Storage volume : 300L • Type : Internal double coil • Material : Stainless steel • Capacity of booster heater : 2.4kW
Installation Kits	Domestic Hot Water Tank Kit	PHLTA (1Ø, Split)		Domestic Hot Water Heating	To operate with DHW tank	• Parts included : DHW tank sensor (Thermistor), Circuit breaker, Relay
		PHLTC (3Ø, Split)				
		PHLTB (Monobloc)				• Parts included : DHW tank sensor (Thermistor), Circuit breaker, Relay, Multi harness
	Solar Thermal Kit	PHLLA		Solar Thermal Heat Utilization	To operate with solar thermal system	• Length of thermistor : 12m • Size of tube connector (W x H x D) : 110 x 55 x 22

Category	Model Name	Model Number	Figure	Relevant Function	Purpose	Feature
Installation Kits	Electric Back up heater (for Monobloc)	HA031M E1		Capacity back up & Emergency Operation	To supplement insufficient capacity	• Heater capacity : 3kW • Number of heating coil : 1EA (3.0kW) • Size (W x H x D) : 210 x 607 x 220 • Power : 220 - 240V, 1Ø
		HA061M E1				• Heater capacity : 6kW • Number of heating coil : 2EA (3.0 + 3.0kW) • Size (W x H x D) : 210 x 607 x 220 • Power : 220 - 240V, 1Ø
		HA063M E1				• Heater capacity : 6kW • Number of heating coil : 3EA (2.0 + 2.0 + 2.0kW) • Size (W x H x D) : 210 x 607 x 220 • Power : 380 - 415V, 3Ø
ETC	Extension wire for wire remote controller	PZCWRC1		-	To extend wire between wired remote controller and indoor unit	• Length : 10m
	Extension cable for Wi-Fi Modem	PWYREW000		Wi-Fi Control via LG ThinQ	To extend wire between Wi-Fi modem and indoor unit	• Length : 10m
	2-Remo Control Wire	PZCWRC2		2-Remote Control	To connect two remote controller on the one indoor unit	• Length : 0.25m • Service part
	Drain pan (for Split IDU)	PHDPB		Cooling Operation	To collect condensed water in indoor unit when cooling operation	-
	Cover plate (for Split IDU)	PDC-HK10		-	To fill the blank space of the indoor unit front panel when the remote controller is relocated indoors.	-

# ACCESSORIES

## Accessories Provided by LG

Category	Model Name	Model Number	Figure	Relevant Function	Purpose	Feature
Remote Controller	Wired Remote Controller	PREMTW101		2-Remote Control	To control AWHP using two remote controller (Additional remote controller)	<ul style="list-style-type: none"> <li>New modern design 4.3 inch color LCD display.</li> <li>Information displayed with simple graphic, icon &amp; text.</li> <li>Built-in temperature sensor</li> <li>Size (W x H x D) : 120 x 120 x 16</li> <li>Extension cable (PZCWRC1, 10m) and 2-remo cable (PZCWRC2, 0.25m) are included.</li> </ul>
Central Controller	AC Ez Touch	PACEZA000		Centralized Control	To control AWHP using LG central controller	<ul style="list-style-type: none"> <li>5 inch color display</li> <li>User-friendly control with iconographic interface (Touch screen)</li> <li>Max 64 unit control</li> <li>Total 200 schedule events (Weekly/Monthly/Yearly/Exception day)</li> <li>Operation history</li> <li>Remote controller lock (All, Temp, Mode)</li> <li>PC access supported (IPv6 supported)</li> <li>DI 1EA (Emergency stop only)</li> <li>Size (W x H x D) : 137 x 121 x 25</li> </ul>
	AC Smart 5	PACSSA000				<ul style="list-style-type: none"> <li>10.2 inch color display</li> <li>User-friendly control with iconographic interface (Touch screen)</li> <li>Max 128 unit control</li> <li>Total 100 schedule events (Weekly/Monthly/Yearly/Exception day)</li> <li>History / Operation trend</li> <li>Interlock with 3<sup>rd</sup> party equipment (ACS IO, ACU IO Module is needed)</li> <li>Error alarm by e-mail</li> <li>Remote controller lock (All, Temp, Mode)</li> <li>Map view (Visual navigation)</li> <li>Web access supported with HTML5 (PC, Smartphone, Tablet)</li> <li>DI 2EA, DO 2EA</li> <li>BACnet IP / Modbus TCP protocol support</li> <li>Size (W x H x D) : 253.2 x 167.7 x 28.9</li> </ul>
	ACP 5	PACP5A000				<ul style="list-style-type: none"> <li>Web access controller</li> <li>Max 256 unit control</li> <li>Total 100 schedule events (Weekly/Monthly/Yearly/Exception day)</li> <li>History / Operation Trend</li> <li>Interlock with 3<sup>rd</sup> party equipment (ACS IO, ACU IO Module is needed)</li> <li>Error alarm by e-mail</li> <li>Remote controller lock (All, Temp, Mode)</li> <li>Map view (Visual navigation)</li> <li>DI 10EA, DO 4EA</li> <li>BACnet IP / Modbus TCP protocol support</li> <li>Size (W x H x D) : 270 x 155 x 65</li> </ul>
Gateway	ACP Lonworks	PLNWKB000		Centralized Control	To link with AWHP and other existing building control system	<ul style="list-style-type: none"> <li>Web access controller</li> <li>Max 64 unit control</li> <li>ACP function included</li> <li>Lonworks protocol support</li> </ul>

Category	Model Name	Model Number	Figure	Relevant Function	Purpose	Feature
Gateway	Modbus RTU	PMBUSB00A		Centralized Control	To communicate and control through the central controller (Providing Modbus RTU connection between AWHP and BMS)	<ul style="list-style-type: none"> <li>Modbus RTU slave (RS485) / 9,600 bps</li> <li>Size (W x H x D) : 53.6 x 89.7 x 60.7</li> <li>Max 16 IDUs with single module / Max 64 IDUs with 4 modules</li> <li>Power : DC 12V</li> </ul>
	PI485 Gateway (for Mono & Split)	PMNFP14A1 <sup>1)</sup>			To communicate and control through the central controller (Converting LG protocol to RS485 protocol)	<ul style="list-style-type: none"> <li>1 for each outdoor unit</li> <li>Power : Supplied by outdoor unit</li> </ul>
	PI485 Gateway (for IWT type)	PP485B00K <sup>2)</sup>			To communicate between outdoor unit and IWT type indoor unit	<ul style="list-style-type: none"> <li>1 for each outdoor unit</li> <li>Power : Supplied by outdoor unit</li> </ul>
Dry Contact	Simple Dry Contact	PDRYCB000		-	To connect between the AWHP and external devices to control various functions	<ul style="list-style-type: none"> <li>1 Set per 1 unit</li> <li>1 Input contact for turning On/Off</li> <li>Input power : 220 ~ 240V</li> <li>2 Output contacts                             <ul style="list-style-type: none"> <li>Operation status</li> <li>Error status</li> </ul> </li> </ul>
	Dry Contact for Thermostat	<b>NEW</b> PDRYCB320 <sup>3)</sup>				<ul style="list-style-type: none"> <li>1 Set per 1 unit</li> <li>Non voltage or 12 ~ 24V</li> <li>1 Analog input for set point                             <ul style="list-style-type: none"> <li>On/Off, Operation mode, DHW heating</li> <li>Emergency mode, Silent mode</li> </ul> </li> <li>2 Output contacts                             <ul style="list-style-type: none"> <li>Operation status</li> <li>Error status</li> </ul> </li> </ul>
ETC	LG Wi-Fi Modem	PWFMD200		Wi-Fi Control via LG ThinQ	To control AWHP via smartphone	<ul style="list-style-type: none"> <li>Basic control function                             <ul style="list-style-type: none"> <li>On/Off, Operation mode, Set temp</li> <li>DHW heating and Set temp</li> <li>Weekly On/Off schedule</li> </ul> </li> <li>Error status check</li> <li>Frequency : 2.4GHz</li> <li>IEEE 802.11b/g/n supported</li> </ul>
	Meter Interface	PENKTH000		Energy Monitoring	To measure production / Consumption power	<ul style="list-style-type: none"> <li>Energy meter interface to monitor Electricity and Heat energy                             <ul style="list-style-type: none"> <li>Max 3 watt</li> <li>hour meter</li> <li>Max 1 heat meter</li> <li>Pulse width : 40ms ~ 100ms</li> </ul> </li> <li>Modbus RTU comm. with THERMA V                             <ul style="list-style-type: none"> <li>2 wire RS485 / 9600bps</li> </ul> </li> <li>Power : DC 12V</li> <li>Size (W x H x D) : 54 x 90 x 61</li> </ul>
	2 Zone Valve Controller	PZNVVB200		Zone Valve Control	To control individual zone valves with room temperature sensor or room thermostat	<ul style="list-style-type: none"> <li>Individual temperature setting possible. (To be set through wired remote control in room temperature input mode)</li> <li>Room temperature detection (AI : 2 ports)</li> <li>3<sup>rd</sup> party thermostat interlock input. (DI : 2 port)</li> <li>Can read one DI or AI for each zone.</li> <li>Maximum number of connections : Max 4EA (Expandable up to 8-zone)</li> <li>Size (W x H x D) : 53.6 x 89.7 x 60.7</li> <li>Power : DC12V for Module, AC24V for valve</li> </ul>


Note  
 1. PI485 Gateway (PMNFP14A1) should be installed on outdoor unit to use Central controller.  
 2. PI485 Gateway (for IWT type, PP485B00K) is required for communication between outdoor unit and indoor unit. (Install at outdoor unit)  
 3. Available from April 2020.

## LG Wi-Fi Modem

PWFMDD200 ENCXLEU

Access LG THERMA V anytime and from anywhere with Wi-Fi equipped device. LG's exclusive Home Appliances control app (LG ThinQ) is available. Simple operation for various functions.

- On/Off
- Operation mode selection
- Current temperature
- Set temperature
- On/Off reservation
- Energy monitoring



Model Name	PWFMDD200
Size (mm)	46 x 68 x 14
Interfaceable Products	THERMA V Split & Monobloc
Connection Type	Indoor Unit 1 : 1
Communication Frequency	2.4GHz
Wireless Standards	IEEE 802.11b/g/n
Mobile Application	LG ThinQ (Android v4.1 (Jellybean) or higher, iPhone iOS 9.0 or higher)
Optional Extension Cable	PWYREW000 (10m extension)

Note

1. Functionality may be different according to each Indoor model. (Split and Monobloc available)
2. User interface of application shall be revised for its design and contents improvement.
3. Application is optimized for smartphone use, so it may not be well functioning with tablet devices.
  - For the compatibility with indoor unit, please contact regional office.

## Domestic Hot Water Tank

OSHW-200F AEU  
 OSHW-300F AEU  
 OSHW-500F AEU  
 OSHW-300FD AEU



Domestic Hot Water Tank		Unit	OSHW-200F	OSHW-300F	OSHW-500F	OSHW-300FD
General Characteristics	Water Volume	L	200	300	500	300
	Diameter	mm	640	640	640	640
	Height	mm	1,350	1,850	1,900	1,850
	Empty Weight	Kg	61	100	146	106
	Tank Materials	-	STS : F18	STS : F18	STS : F18	STS : F18
Specification of Electric Back up	Color	-	Grey	Grey	Grey	Grey
	Additional Electric Heater	W	2,400	2,400	2,400	2,400
	Power Supply	V, Ø, Hz	230, 1, 50 (60)	230, 1, 50 (60)	230, 1, 50 (60)	230, 1, 50 (60)
Specification of Heat Exchanger	Adjustable Thermostat	°C	0 - 90	0 - 90	0 - 90	0 - 90
	Exchanger Type	-	Single	Single	Single	Double
	Material Exchanger	-	STS : F18	STS : F18	STS : F18	STS : F18
	Maximum Water Temp	°C	90	90	90	90
Water Connections	Coil Surface	m <sup>2</sup>	2.3	3.1	4.8	3.1 + 0.97
	Heat Pump Inlet	inch	1 BSP female	1 BSP female	1 ¼ BSP female	¾ BSP female (Upper coil)
	Heat Pump Outlet	inch	1 BSP female	1 BSP female	1 ¼ BSP female	¾ BSP female (Upper coil)
	Solar Inlet	inch	-	-	-	1 BSP Female (Lower coil)
	Solar Outlet	inch	-	-	-	1 BSP Female (Lower coil)
	City Water Inlet	inch	¾ BSP male	¾ BSP male	1 BSP male	¾ BSP male
Energy Efficiency Class (A+ to F Scale)	Hot Water Outlet	inch	¾ BSP female	1 BSP female	1 BSP female	1 BSP female
	Standing Heat Loss	W	61	70	83	70

Mandatory Optional Accessories	
Domestic Hot Water Tank Installation Kit	PHLTA (1Ø, Split), PHLTB (Monobloc), PHLTC (3Ø, Split)
Optional Accessories	
Thermostatic Mixing Valve (3/4" DN20)	OSHA-MV
Thermostatic Mixing Valve (1" DN25)	OSHA-MV1
3Way Valve	OSHA-3V

## Combined Test with DHW Tank

LG has conducted a combination test of THERMA V with DHW tanks in accordance with EN16147 and obtained an ErP label for packages in order to cope with European nZEB regulations.

- R32 Monobloc (5, 7, 9kW) + OSHW-200F
- R32 Monobloc (12, 14, 16kW) + OSHW-200F
- R32 Monobloc (5, 7, 9kW) + OSHW-300F
- R32 Split Hydro Box (5, 7, 9kW) + OSHW-200F



Model	AWHP	R32 Split (5, 7, 9kW)	R32 Monobloc (5, 7, 9kW)	R32 Monobloc (12, 14, 16kW)	R32 Monobloc (5, 7, 9kW)
	IDU	HM0916M NK4	HM051M U43	HM121M U33	HM051M U43
	ODU	HU051MR U44 HU071MR U44 HU091MR U44	HM071M U43 HM091M U43	HM141M U33 HM161M U33	HM071M U43 HM091M U43
	Tank	OSHW-200F AEU	OSHW-200F AEU	OSHW-200F AEU	OSHW-300F AEU
Declared Load Profile		L	L	L	XL
Average Climate	Grade	A+	A+	A	A+
	Efficiency	118%	122%	109%	134%
	Annual Energy Consumption	865kWh	839kWh	940kWh	1,254kWh
Energy Label					