

■ Cooling Only, Heat Pump

Model Name				AMNQ09GL1A0	AMNW09GL1A2
Power Supply			V, Ø, Hz	220-240, 1, 50	220, 1, 60
Power Input			W	50	
Running Current			A	0.40	
Dimensions	Body	W x H x D	mm	700 x 190 x 700	
		W x H x D	inch	27-9/16 x 7-15/32 x 27-9/16	
Net Weight			kg	15.9	
Shipping Weight			kg	20.5	
Heat Exchanger	(Row x Column x Fins per inch) x No.		-	(2 x 11 x 14) x 1	
	Face Area		m ² (ft ²)	0.12 (1.32)	
Fan	Type		-	Sirocco	
	Air Flow Rate	High-static Mode (Factory Set)	H / M / L	m ³ /min	9.0 / 7.0 / 5.5
			H / M / L	ft ³ /min	318 / 247 / 194
		External Static Pressure	Pa (mmAq)	24.5 (2.5)	
Fan Motor	Type		-	BLDC	
	Output		W x No.	19 x 1	
Dehumidification Rate			l / h (pts/h)	1.1 (2.3)	
Sound Pressure Level		H / M / L	dB(A)	30 / 26 / 23	
Sound Power Level		Max.	dB(A)	49	
Piping Connections	Liquid		mm(inch)	Ø 6.35 (1/4)	
	Gas		mm(inch)	Ø 9.52 (3/8)	
	Drain (O.D. / I.D.)		mm(inch)	Ø 32.0(1-1/4) / 25.0(31/32)	
Safety Devices			-	Fu	
Power and Communication Cable (included Earth)			No. x mm ² (AWG)	4C x 0.75 (18)	

AMNQ12GL2A0 AMNW12GL2A2	AMNQ18GL2A0 AMNW18GL2A2	AMNQ24GL3A0 AMNW24GL3A2
220-240, 1, 50	220-240, 1, 50	220-240, 1, 50
220, 1, 60	220, 1, 60	220, 1, 60
95	120	150
0.80	0.80	1.00
900 x 190 x 700	900 x 190 x 700	1,100 x 190 x 700
35-7/16 x 7-15/32 x 27-9/16	35-7/16 x 7-15/32 x 27-9/16	43-5/16 x 7-15/32 x 27-9/16
20.6	20.6	24.2
25.8	25.8	29.9
(2 x 11 x 18) x 1	(2 x 11 x 18) x 1	(3 x 11 x 18) x 1
0.17 (1.81)	0.17 (1.81)	0.21 (2.31)
Sirocco	Sirocco	Sirocco
10.0 / 8.5 / 7.0	15.0 / 12.5 / 10.0	20.0 / 16.0 / 12.0
353 / 300 / 247	530 / 441 / 353	706 / 565 / 424
24.5 (2.5)	24.5 (2.5)	24.5 (2.5)
BLDC	BLDC	BLDC
19 x 1 + 5 x 1	19 x 1 + 5 x 1	19 x 2
1.2 (2.6)	1.7 (3.6)	2.2 (4.7)
31 / 28 / 27	36 / 34 / 31	39 / 35 / 32
52	54	58
Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)*
Ø 9.52 (3/8)	Ø 12.7 (1/2)	Ø 12.7 (1/2)*
Ø 32.0(1-1/4) / 25.0(31/32)	Ø 32.0(1-1/4) / 25.0(31/32)	Ø 32.0(1-1/4) / 25.0(31/32)
se	Fuse	
-	-	
4C x 0.75 (18)	4C x 0.75 (18)	4C x 0.75 (18)