Artistic Space beyond Display LG OLED Signage 55EF5E

Actual on-site appearance may differ from the above simulated scene.



Blending in with the space while stamped on everyone's mind. With LG OLED signage, discover unprecedentedly flexible design. Beyond its informative features, LG OLED signage delivers unsurpassed advertising effectiveness, redesigning space as a prestige-enhancing landmark with perfect colors and innovative forms.

Actual on-site appearance may differ from the above simulated scene.

Unrivaled Picture Quality



Perfect Black

LCD

Limitless contrast and the deepest blacks Self-lighting pixels switch off completely to reproduce absolutes blacks with no light bleed, offering infinite contrast.



Accurate & stable color reproduction Self-lighting pixels bring colors to life with superb accuracy.



Perfect Viewing Screen

Wide viewing angle

LG OLED Signage delivers awe-inspiring picture quality across the entire screen, even from wide viewing angles.



LG OLED Signage





Space-fitting Design



Perfect Design

LG's OLED technology unlocks the new worlds of design flexibility with unbelievably lightweight and slim display.



Expandable Display Area

The total display area can be as large as you want by tiling up displays horizontally and vertically. This provides viewers with incredible immersion in their viewing experience.





Slim

Curved

m



Lightweight

Flexible





Space-fitting Design

Variety of Curvatures for Landmarks

The 55EF5E series supports a various concave and convex curvatures in both portrait and landscape orientations. It can be positioned in a variety of ways to keep passengers captivated.

In Portrait



Max Curvature in Portrait • Concave/Convex: up to 1,000R

In Landscape



Max Curvature in Landscape

Concave/Convex: up to 1,000R

What is R?

Due to the nature of its curved design; "R" signifies the radial length of a circle which allows for its curved display. For example, displays with a curvature of 1,000R will have a radius of 1m (1,000mm)




Design Flexibility



On-site Customization

The 55EF5E enables a completely new approach for innovative and flexible designs. Its optional "Curvature Calibrator(CC)¹" supports the coordination of displays with various convex and concave curvatures, depending on the requirements. It is possible to rapidly respond to changes on-site, making it easier to successfully build a completely unique and eye-catching landmark.



1) A Curvature Calibrator needs to be purchased separately. Please contact your regional LG sales representatives for details.

Immersive Viewing Experience



Slimmer Bezel

Compared to the previous model, 55EF5E has reduced its bezel size to provide much more immersive and seamless viewing experiences to viewers.






Seam (Portrait/Landscape) 10.0 mm / 15.6 mm 21.0 mm / 15.2 mm




Synced Playback and Management

Using its built-in high performance SoC, each display plays its video tile without lag for synchronized content playback. Also, the LAN daisy chain allows users to control and monitor displays, transmit data and even update firmware all at once.




Dimension

Landscape (Flat, w/ Signage Box)



Portrait (Flat, w/ Signage Box)



* Dimensions may vary depending on the curvature of the display. Please contact your regional LG sales representatives for a precise 2D drawing.

Connectivity (Signage Box)

0	2	8	4	6	6	0	8	9000
 AC IN USB IN 1 	-	P OUT ISB IN 2	9 IR IN10 RS23					
3 HDMI IN4 DP IN		AN IN AN OUT	RS23 RS23 AUDIO	2C OUT				

Specifications 55EF5E Screen Size Panel Technology OLED Aspect Ratio 16:9 Native Resolution 1,920 x 1,080 (FHD) 400/150 nits (APL¹ 25%/100%) Brightness PANEL Contrast Ratio 150,000:1 Viewing Angle (H x V) 178 x 178 30.000 Hrs Life Time (Typ.) **Operation Hours** 18 Hrs / 7 Days (Moving Video Only) Landscape & Portrait Orientation Input HDMI, DP, USB 2.0 (2) CONNECTIVITY Output DP, Audio (Fixed/Off/Variable) External Control RS232C In/out, RJ45 In/out, IR In Bezel Color Black Landscape: 0.6 / 0.6 / 6.7 / 6.7 mm (Flat, Off Bezel) Portrait: 0.6 / 0.6 / 6.7 / 6.7 mm (Flat, Off Bezel) Bezel Width (T/B/L/R) Landscape: 5.0 / 10.6 / 7.6 / 7.6 mm (Flat, On Bezel) Portrait: 5.0 / 5.0 / 7.8 / 13.2 mm (Flat, On Bezel) Landscape: 48.2" x 27.4" x 1.5" / 1,224.9 x 696.2 x 38.0 mm (Head, w/Pem-nut) Portrait: 27.6" x 48" x 1.5" / 701.4 x 1,219.7 x 38.0 mm (Head, w/Pem-nut) Landscape: 48.2" x 27.4" x 0.5" / 1,224.9 x 696.2 x 12.4 mm (Head Only) Portrait: 27.6" x 48" x 0.5" / 701.4 x 1,219.7 x 12.4 mm (Head Only) Signage Box: 16.3" x 13.9" x 2.3" / 413 x 353 x 57.3 mm Monitor Dimension PHYSICAL $(W \times H \times D)$ SPECIFICATION Landscape: 21.8 lbs / 9.9 kg (Set) Portrait: 21.8 lbs / 9.9 kg (Set) Signage Box: 7.7 lbs / 3.5 kg Weight Carton Dimensions 1,350 x 837 x 250 mm $(W \times H \times D)$ Landscape: 37.5 lbs / 17 kg | Portrait: 37.5 lbs / 17 kg Packed Weight Internal Memory (64GB), Temperature Sensor, webOS 3.0+, USB Auto Playback, Local Contents Scheduling, Group Manager, Failover (USB/DP/HDM/Internal Memory), Content Sync (RS232C/Local Network), Video Taq(2), OSD/Content Rotation, Gapless Playback, Tile Mode, Setting Data (Loning, Firmware Update by Network, SNMP, ISM Mode, DPM, Wake on LAN, HDMI-CEC², Crestron Connected¹³ SPECIAL FEATURES ENVIRONMENT Operation Temperature 32°F to 104°F / 0°C to 40°C CONDITIONS Operation Humidity 10% to 80% Power Supply 100-240V~, 50/60Hz POWER Power Type Built-In Power Power Consumption Typ. / Max. 309 W⁴ / 318 W⁴ Safety IEC 60950-1 / EN 60950-1 / UL 60950-1 CERTIFICATION EMC FCC Class "A" / CE / KCC ErP / Energy Star Yes / No MEDIA PLAYER OPS Type Compatible No COMPATIBILITY External Media Player Attachable Yes SOFTWARE Content Management Software SuperSign CMS COMPATIBILITY Control and Monitoring Software SuperSign Control+ / Control Remote Controller (2 Batteries Included), Power Cord, QSG, IR Receiver, Regulation Book,

1) Average Picture Level 2) Compatibility may differ by equipment. 3) Network Based Control 4) Based on 8 color bar

ttp://www.lg.com/us/business/commercial-display

- ttp://www.twitter.com/LGCommDisplays
- fthttp://www.facebook.com/LGcommercialdisplays

bttp://www.linkedin.com/company/lg-commercial-displays-usa

Chttp://www.youtube.com/lgcommercialdisplayusa

LG may make changes to specifications and product descriptions without notice.

Copyright © 2018 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp. The names of products and brands mentioned here may be the trademarks of their respective owners. SPEC_55EF5E_061828_PR

ACCESSORIES

Basic

Optional



Phone to RS232C Gender, RS232 Cable (4p-4p), FFC Cables (220mm x 4ea for Connection between Panel and

Signage Box), DP Cable, LAN Cable, LC (VLC Cable)

Curvature Calibrator (ACC-CC-EF5E)