

## 21.8 cu. ft. 30" Wide French Door Refrigerator



- 30" Width
- 22 cu. ft. Capacity
- Smart Cooling® System
- LED Lighting
- SmartPull™ Freezer Handle
- Factory Installed Ice Maker
- LoDecibel™ Quiet Operation
- Auto Closing Door Hinge
- SmartDiagnosis™



### COLOR AVAILABILITY

● LFC22770ST – Stainless Steel

### CAPACITY

Refrigerator (cu. ft.)	14.5
Freezer (cu. ft.)	7.3
Total Capacity (cu. ft.)	21.8

### ENERGY

Energy Consumption (kWh / Year)	587
ENERGY STAR® Qualified	Yes

### WATER & ICE SYSTEM

Ice & Water Dispenser	No
Dual Ice Maker	No
Ice System	Factory Installed Ice Maker
Daily Ice Production	2.8 lbs.
IcePlus™ Production	3.1 lbs.
Ice Storage Capacity	12 lbs.
Water Filter	No

### COOLING

Compressor Type	Linear Compressor
Dual Evaporators	No
Cooling System	Smart Cooling®
Multi-Air Flow™ System	Yes
Door Cooling+	No
Temperature Sensors	4
Fresh Air Filter	No

### CONVENIENCE

Display Type	Membrane / White LED
Temperature Controls	Electronic / Digital
Door Alarm	Yes
Child Lock	No
Auto Closing Door Hinge	Yes
ADA Compliant	No
Sabbath Mode	No
LoDecibel™ Quiet Operation	Yes

### REFRIGERATOR

No. of Shelves	4 Split
Cantilevered Shelves	Yes
Shelf Construction	Spill Protector™ Tempered Glass
Crisper Bins	2 Humidity Crispers
Glide N' Serve™ Pantry Drawer	Yes
Cool Guard	No
Refrigerator Light	Ceiling LED

### REFRIGERATOR DOOR

InstaView™ Door-in-Door®	No
Door-in-Door® with ColdSaver™ Panel	No
No. of Door Bins	8 Total (5 Gallon Sized, 1 Dairy, 2 Half)
Door Bin Construction	2 Pieces (Clear + Opaque)

### FREEZER

Freezer Type	Pull Drawer
Freezer Drawers	2-Tier Organization
DuraBase™ Solid Drawer Base	Yes
Drawer Divider	Yes
Ice Storage	Ice Bin in Freezer
Freezer Light	LED Lighting
Freezer Handle	SmartPull™ Handle

### SMART FEATURES

Wi-Fi Enabled	No
ThinQ®	No
SmartDiagnosis™	Yes

### MATERIALS AND FINISHES

Hidden Hinges	Yes
Surface	Smooth
Fingerprint & Smudge Resistant Exterior	No
Handles	Matching Handles

### TECHNICAL SPECS

Required Power Supply	115 V, 60 Hz, 15 Amp
Plug Type	3-Prong
Power Cord Location	Back
Min. / Max. Water Pressure	20 – 120 psi

### DIMENSIONS / CLEARANCES / WEIGHTS

Depth with Handles	35 1/2"
Depth without Handles	33"
Depth without Door	29"
Depth (Total with Door Open)	44 3/4"
Height to Top of Case	67 1/4"
Height to Top of Door Hinge	68 1/2"
Width	29 3/4"
Width (Door Open 90° with Handle)	38 1/4"
Width (Door Open 90° without Handle)	33 1/4"
Door Edge Clearance with Handle	4 1/4"
Door Edge Clearance without Handle	2"
Installation Clearance	Sides 1/8", Top 1", Back 2"
Approx. Weight (Product / Carton)	237 lbs. / 259 lbs.
Carton Dimensions (WxHxD)	31 1/2" x 69 3/8" x 37 3/4"



### LIMITED WARRANTY

Parts & Labor	1 Year
Sealed System (Parts & Labor)	5 Years
Compressor (Parts & Labor)	5 Years
Linear / Inverter Compressor (Parts Only)	10 Years



\*System tested and certified by NSF® International against NSF / ANSI Standard 42, Standard 53 and Standard 401.

### DIMENSIONS / CLEARANCES



### DIMENSIONS / CLEARANCES

A	Depth without Handles	33" (838 mm)
B	Width	29 3/4" (756 mm)
C	Height to Top of Case	67 1/4" (1708 mm)
D	Height to Top of Hinge	68 1/2" (1740 mm)
E	Back Clearance	2" (51 mm)
F	Depth without Door	29" (737 mm)
G	Depth (Total with Door Open 90°)	44 3/4" (1137 mm)
H	Front Clearance	24" (610 mm)
I	Depth with Handle	35 1/2" (902 mm)

### INSTALLATION NOTES

- The installation location chosen for the refrigerator should allow space behind the unit for connections and airflow and space in front to open the doors and drawers.
- Too small of a distance from adjacent items may result in lowered freezing capability and increased electricity consumption charges. Allow at least 24 inches (610 mm) in front of the refrigerator to open the doors, and at least 2 inches (50.8 mm) between the back of the refrigerator and the wall.