28BQ750-C DualUp 16:18 Monitor





FEATURES

27.6" 16:18 ULTRA-TALL IPS DISPLAY PROVIDES HIGH-RESOLUTION IMAGES (2560 X 2880) AND A DOUBLE-HEIGHT VIEWING SCREEN

An impressive 16:18 monitor that features LG's IPS screen technology and QHD (2560x2880) resolution delivers crisp images and a large, long viewing surface aimed at upgrading your productivity.

LG'S IPS DISPLAY WITH DCI-P3 98% (TYP.) DELIVERS OUTSTANDING COLOR REPRODUCTION OVER A WIDE VIEWING ANGLE

Thanks to LG's advanced IPS screen technology, images remain crisp and sharp over a wide 1780 viewing angle. Colors are faithfully reproduced, thanks to the ability to cover 98% (typ) of the DCI-P3 color spectrum.

HDR10 CAPABILITY PROVIDES OUTSTANDING IMAGES WHEN VIEWING HDR10 CONTENT

HDR10 can deliver a dramatic visual experience with enhanced contrast and detail for a more immersive viewing experience.

MAXXAUDIO®

7W Stereo Speakers with MaxxAudio $^{\otimes}$ sound compliment the display to deliver a more immersive experience.

CONVENIENT USB TYPE-C[™] CONNECTIVITY

USB Type-C[™] ports can simultaneously allow 4K display, data transfer, and connected device charging (90W) through a single cable.

SPECIFICATIONS

27.6" DualUp (2560 x 2880) IPS Display 300 nits (Typ.) Brightness DCI-P3 98% (CIE1976) Color Gamut 5ms (GtG at Faster) Response Time HDR10 Color Calibrated

Display Position Adjustments: Tilt/Height/Swivel

www.LG.com/us/commercial



28BQ750-C DualUp 16:18 Monitor

CATEGORY	SPEC ITEMS	28BQ750-C	CATEGORY	SPEC ITEMS	28BQ750-C
DISPLAY	Size (Inches)	27.6 Inch		HDMI	YES(2ea)
	Resolution	2560 x 2880		HDMI Version	2.0
	Panel Type	IPS	CONNECTIVITY	HDMI (HDCP Version)	2.2
	Backlight Technology	LED		HDMI (V Frequency)	60Hz
	Backlight Type	Edge		HDMI (FreeSync Supported Frequency)	N/A
	Backlight Array	H1B		HDMI (Max. Resolution at Hz)	2560 x 2880 @ 60Hz
	Backlight Dimming Technology	Global Dimming		DisplayPort	YES(1ea)
	Aspect Ratio	16:18		DP Version	1.4
	Pixel Pitch	0.18195 x 0.18195mm		DP (HDCP Version)	2.2
	Brightness (Min.)	240 nits		DP (V Frequency)	60Hz
	Brightness (Typ.)	300 nits		DP (FreeSync Supported Frequency)	N/A
	Color Gamut (Min.)	DCI-P3 90% (CIE1976)		DP (Max. Resolution at Hz)	2560 x 2880 @ 60Hz
	Color Gamut (Typ.)	DCI-P3 98% (CIE1976)		USB-C	YES(1ea)
	Color Depth (Number of Colors)	1.07B		USB-C (DP Version)	1.4
	Color Bit	10bit (8bit+FRC)		USB-C (HDCP Version)	2.2
	Contrast Ratio (Min.)	700:1		USB-C (V Frequency)	60Hz
	Contrast Ratio (Typ.)	1000:1		USB-C (Max. Resolution at Hz)	2560 x 2880 @ 60Hz
	Contrast Ratio with DFC	Mega		USB-C (DP Alternate Mode)	YES
	Response Time	5ms (GtG at Faster)		USB-C (Data Transsmission)	YES
	Viewing Angle (CR≥10)	178°(R/L), 178°(U/D)		USB-C (Power Delivery)	90W
	Surface Treatment	Anti-Glare		USB Upstream Port	YES(1ea/ver2.0)
FEATURES	HDR 10	YES		USB Downstream Port	YES(2ea/ver3.0)
	HDR Effect	YES		Headphone out	YES
	Nano IPS™ Technology	YES		[Location]	Rear
	Wide Color Gamut	YES	MECHANICAL	Borderless Design	3-Side Virtually Borderless Design
	Color Calibrated	YES		Color (Front Cabinet)	Charcoal gray Texture
	Auto Brightness	YES		Color (Middle Cabinet)	Charcoal gray Texture
	Flicker safe	YES		Color (Back Cover)	Charcoal gray Texture
	Picture Mode	(Non HDR Contents)> Custom, Vivid, HDR Effect, Reader, Cinema, FPS, RTS, Color Weakness		Color (Stand Body)	Black Texture
	Reader Mode	YES		Color (Stand Base)	Black Texture
	Color Weakness	YES		Display Position Adjustments	Tilt/Height/Swivel
	Super Resolution+	YES		Tilt	-25 to 25°
	Black Stabilizer	YES		Swivel	-30 to 30°
	Dynamic Action Sync	YES		Height Range	3.1 in. / 80 mm
	User Define Key	YES		Wall Mountable	100 x 100 mm
	Auto Input Switch	YES		Base Detchable	YES
	PBP	YES (2PBP)		Assembly Step	Two-Step
		17 languages (English, German, French, Spanish, Italian, Swedish, Finnish, Portuguese,		OneClick Stand	YES
	Onscreen Display Languages	Portuguese(brazil), Polish, Russian, Greek, Ukrainian, Chinese, Traditional Chinese, Japanese, Korean)		Dimensions (W x H x D)	18.9 x 21.6 x 1.8 in. / 481.5 x 549.5 x 44.9 mm
	Other Features	Low Blue Light, Built-in KVM			19.0 x 26.3 x 9.8 in. / 481.5 x 667.6 x 250 mm
	Dual Controller	YES		Dimensions with Stand Up (W x H x D)	
				Dimensions with Stand Down (W x H x D)	19.0 x 23.1 x 9.8 in. / 481.5 x 587.6 x 250 mm
	OnScreen Control / Switch	YES		Shipping Dimensions (W x H x D)	28.2 x 21.9 x 7.4 in. / 717 x 557 x 189 mm
SOUND	Built-in Speakers	YES		Weight	9.5 lbs. / 4.3 kg
	Speaker_Output (unit)	7W		Weight with Stand	15.7 lbs. / 7.1 kg
	Speaker_Channel	2ch		Shipping Weight	24.0 lbs. / 10.9 kg
	Speaker_Direction	Down Firing		Pallet Stuffing (20ft/40ft/40ft HC)	352ea / 704ea / 768ea
	Maxx Audio	YES		Warranty	3 Year Limited
ELECTRICAL	Power Supply Type	External Power(Adapter)	WARRANTY & ACCESSORIES	Adapter	YES
	AC Input	100-240Vac, 50/60Hz			Black
	DC Output	19.5V 10.8A		Adapter (Color)	
	Power Consumption (Typ.)	40W		Power Cord	YES
	Power Consumption (Max.)	40W 190W		Power Cord (Color/Length)	Black / 1.5m
				HDMI	YES
	Power Consumption (Energy Star)	28.31W		HDMI (Color/Length)	Black / 2.0m w/ Holder
	Power Consumption (Sleep Mode)	Less than 0.5W		USB Type C	YES
	Power Consumption (DC Off)	Less than 0.3W		USB Type C (Color/Length)	Black / 1.8m w/ Holder
REGULATORY & CERTIFICATIONS	EPA 8.0	YES		Calibration Report (Paper)	YES
	UL (cUL)	YES			DC Extension rable (1.4m. Black). Square Stand with Base Assembly. Cable holder
	FCC (Regulatory)	Class "B"		Other Accessories	Warranty Card, ESG, Manual
	EPEAT (USA)	YES			
	Others	ES8.0, CEC `21 (Module spec), TUV			
	1				

www.lg.com/us/business/commercial-display
www.youtube.com/lgcommercialdisplayusa
www.facebook.com/LGcommercialdisplays
www.linkedin.com/company/lg-commercial-displays-usa
www.twitter.com/LGCommDisplays

Copyright 2024 @LG Electronics USA, Inc., 2000 Millbrook Drive LincoInshire, IL 60069, USA. All rights reserved. LG and the LG logo are registered trademarks of LG Corp. All other products and brand names are trademarks or registered trademarks of their respective companies. Designs, features, and specifications are subject to change without notice. All screen images are simulated for illustrative purposes only. SPEC-288Q750-C-0424-3.0A

