Personal Fitness Smart Touch Screen TV

15LS766F

Provide your clients and members with the smart solutions, 15.6" multi-touch based smart TV, for a superior workout experience. The 15LS766F series enables interactive service with its multi-touch screen and webOS operating system. Its industrial panel is durable and will sustain long operation. The LG IPS panel technology provides great viewing angles for multiple viewers in a fitness environment.




Personal Fitness Smart Touch Screen TV

15LS766F

Interactive Fitness TV Solution



This touch screen recognizes the presence of more than two points of contact with the surface, allowing more users in a fitness setting to experience interactive services (e.g., trainer and client) and entertainment.



This TV has an LG IPS Panel which delivers awe-inspring picture quality across the entire screen, even from wide viewing angles. The "Instant On" feature allows immediate TV power-on and picture display with no long boot-up time delay for the client.



Pre-loaded Apps (including gaming apps)

Clients can be served with pre-loaded applications, including many popular games, Youtube, Web Browser and others.

Apps:

• Smartshare

- Parking Panic

Games:

- Screen Share
- Genius MemoryMaya Brick Breaker
- YouTube
- Water Blast
- Arirang TV
- 3 Cats
- Accuweather

• Web Browser

- Balda
- 4 in a ROW
- 2048





UL Certified - Perfect for Public Spaces

The 15LS766F is UL listed to ensure lower operating temperature, lower leakage current and a third wire grounding conductor to provide a product so stringently designed it can even be used in fitness environments.









Personal Fitness Smart Touch Screen TV

15LS766F

Smart Experience



Pro:Centric SMART is optimized for customizing information and entertainment services through an IP & RF infrastructure. With its high picture quality, sophisticated design and advanced connectivity functions, the 15LS766F Series improves and creates new workout experiences for clients, members and staff.

Pro:Centric Direct Solution

Pro:Centric Direct is a content management system that supports simple editing tools and provides various solutions such as 1-click service and IP-network-based remote management. With this solution, clubs are able to customize the user interface while managing the TV content efficiently.

Pro:Idiom

Securely provide entertainment content with Pro: Idiom DRM (Digital Right Management) which prevents illegal copying on your LG devices.


Antimicrobial Properties Applied

Antimicrobial properties applied to the plastic housing of the 15LS766F series conform with the ISO 22196 standard.*

Power Over Coax (PoC)

The 15LS766F can be powered over coax cable which can be routed (along with other cables) through its arm adapter. The arm adapter connects the TV with an optional mounted arm* for ease of viewing in fitness environments where flexible placement is needed to best serve clients and facility needs.












* NOTES

- Antimicrobial properties: : Antimicrobial properties do not protect users against bacteria,
- External plastic housing excludes front LCD panel.
- ISO 22196: Measurement of antimicrobial activity on plastics and other non-porous surfaces.

Dimensions







^{*} Dimensions may differ from the above image, so please contact LG sales team to verify before ordering.

- thttp://www.lg.com/us/business/commercial-display
- http://www.twitter.com/LGCommDisplays
- f http://www.facebook.com/LGcommercialdisplays
- in http://www.linkedin.com/company/lg-commercial-displays-usa
- http://www.youtube.com/lgcommercialdisplayusa

Specifications

15LS766F

	Screen Size	15.6"
	Backlight Type	LED (Edge)
	Resolution	1,920 x 1,080 (FHD)
	Brightness nits	250 (Typ) / 220 (Min)
PANEL	Static (Panel) Contrast Ratio	700 (Typ)
	Viewing Angle (L-R, T-B)	160°, 160°
	Response Time (G to G, ms)	25
	Life Span (hrs) Touch Screen	50,000 10 Point Multi Touch PCAP, Accuracy < 2mm
	Digital (Terrestrial,Cable,Satellite)	ATSC, Clear QAM
	Analog	NTSC
BROADCASTING	Closed Caption	Yes
SYSTEM	MPEG-2 / MPEG-4 H.264 Decoding	Yes
	IPTV Capable	Yes
VIDEO	XD Engine	Yes
	Aspect Ratio	16:9, Original, 4:3, Just Scan
	· ·	-
	Picture Mode	7 modes: Vivid, Standard, APS, Cinema, Sports, Game, Expert (Bright Room), Expert (Dark Room)
AUDIO	Audio Output	2 W + 2 W
	Speaker System	2.0 ch
	Sound Mode	Yes 6 modes: Standard, Cinema, Clear Voice III, Sports, Music, Game
	Clear Voice	Yes
SMART TV SOLUTIONS	Solution Type	Pro:Centric (Smart, V, Direct)
	Data Streaming (IP & RF)	Yes
	RF	Yes (1 Tuner)
	HCAP (GEM/HTML) * Service Carousel (TLX, Firmware)	Yes
	Multicast/Unicast Ready	Yes
	webRTC	Yes
	DRM	Pro:Idiom (S/W)
SMART FEATURES	Ditte	webOS 3.5, Commercial Smart Home, Web Browser, Pre-loaded Apps, SDP Server Compatibility, SoftAP,
		Wi-Fi (bandwidth), Screen Share (Miracast), Smart Share (DLNA), DIAL, Bluetooth Audio Playback, LG Sound Sync / Bluetooth
DEVICE MANAGEMENT FEATURES		Millows Course have been been to be full to the Course (DCAD). A to Off (Class Town Course
FEMIURES		Welcome Screen, Insert Image, Instant On, Full Touch Screen (PCAP), Auto Off / Sleep Timer, Smart Energy Saving, Motion Eye Care, USB Cloning
	Set Bottom	
JACK INTERFACE	Set Bottom Set Rear	Energy Saving, Motion Eye Care, USB Cloning
JACK		Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module)
JACK	Set Rear	Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module) HDMI/HDCP In, LAN (RJ45), IR IN, USB, MPI, DC In, RF/AC In [PoC (Power over Coax)]
JACK	Set Rear VESA	Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module) HDMI/HDCP In, LAN (RJ45), IR IN, USB, MPI, DC In, RF/AC In [PoC (Power over Coax)] 75 x 75 mm
JACK INTERFACE	Set Rear VESA Color Bezel Width	Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module) HDMI/HDCP In, LAN (RJ45), IR IN, USB, MPI, DC In, RF/AC In [PoC (Power over Coax)] 75 x 75 mm Front: Black / Back Black
JACK	Set Rear VESA Color Bezel Width W x H x D (without packing or arm adaptor)	Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module) HDMI/HDCP In, LAN (RI45), IR IN, USB, MPI, DC In, RF/AC In [PoC (Power over Coax)] 75 x 75 mm Front Black / Back: Black 23.5mm (T/L/R) / 59.7mm (B) 15.4" x 11" x 1.8" / 391.4 x 278.6 x 46.1 mm
JACK INTERFACE	Set Rear VESA Color Bezel Width W x H x D (without packing or arm adaptor) W x H x D (with packing, without arm adaptor)	Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module) HDMI/HDCP In, LAN (RJ45), IR IN, USB, MPI, DC In, RF/AC In [PoC (Power over Coax)] 75 x 75 mm Front Black / Back: Black 23.5mm (T/L/R) / 59.7mm (B) 15.4" x 11" x 1.8" / 391.4 x 278.6 x 46.1 mm 18" x 7.9" x 14" / 458.0 x 201.0 x 356.0 mm
JACK INTERFACE	Set Rear VESA Color Bezel Width W × H × D (without packing or arm adaptor) W × H × D (with packing, without arm adaptor) Weight (without packing or arm adaptor)	Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module) HDMI/HDCP In, LAN (R45), IR IN, USB, MPI, DC In, RF/AC In [PoC (Power over Coax)] 75 x 75 mm Front: Black / Back: Black 23.5mm (T/MF, / 59.7mm (B)) 15.4" x 11" x 18" / 391.4 x 278.6 x 46.1 mm 18" x 7.9" x 14" / 458.0 x 201.0 x 356.0 mm 6.4 lbs / 2.9 kg
JACK INTERFACE	Set Rear VESA Color Bezel Width W x H x D (without packing or arm adaptor) W x H x D (with packing, without arm adaptor) Weight (without packing or arm adaptor) Weight (without packing, with arm adaptor)	Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module) HDMI/HDCP In, LAN (RJ45), IR IN, USB, MPI, DC In, RF/AC In [PoC (Power over Coax)] 75 x 75 mm Front: Black / Back: Black 23.5mm (T/L/R) / 59.7mm (B) 15.4" x 11" x 1.8" / 39.14 x 278.6 x 46.1 mm 18" x 7.9" x 14" / 458.0 x 201.0 x 356.0 mm 6.4 lbs / 2.9 kg 8.0 lbs / 3.7 kg
JACK INTERFACE	Set Rear VESA Color Bezel Width W x H x D (without packing or arm adaptor) W x H x D (with packing, without arm adaptor) Weight (without packing or arm adaptor) Weight (without packing, with arm adaptor) Weight (including packing and arm adaptor)	Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module) HDMI/HDCP In, LAN (RJ45), IR IN, USB, MPI, DC In, RF/AC In [PoC (Power over Coax)] 75 x 75 mm Front: Black / Back: Black 23.5mm (T/L/R) / 59.7mm (B) 15.4" x 11" x 1.8" / 391.4 x 278.6 x 46.1 mm 18" x 7.9" x 14" / 458.0 x 201.0 x 356.0 mm 6.4 lbs / 2.9 kg 8.0 lbs / 3.7 kg 9.9 lbs / 4.5 kg
JACK INTERFACE	Set Rear VESA Color Bezel Width W x H x D (without packing or arm adaptor) W x H x D (with packing, without arm adaptor) Weight (without packing or arm adaptor) Weight (without packing with arm adaptor) Weight (including packing and arm adaptor) Optional Adapter (AM-PW18BA)	Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module) HDMI/HDCP In, LAN (RJ45), IR IN, USB, MPI, DC In, RF/AC In [PoC (Power over Coax)] 75 x 75 mm Front: Black / Back: Black 23.5mm (T/L/R) / 59.7mm (B) 15.4" x 11" x 1.8" / 391.4 x 278.6 x 46.1 mm 18" x 7.9" x 14" / 458.0 x 201.0 x 356.0 mm 6.4 lbs / 2.9 kg 8.0 lbs / 3.7 kg 9.9 lbs / 4.5 kg Input: 100V - 240V AC 50/60Hz, Output: 19V DC 3.42A
JACK INTERFACE MECHANICAL	Set Rear VESA Color Bezel Width W x H x D (without packing or arm adaptor) W x H x D (with packing, without arm adaptor) Weight (without packing or arm adaptor) Weight (without packing or arm adaptor) Weight (including packing and arm adaptor) Optional Adapter (AM-PW18BA) Max	Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module) HDMI/HDCP In, LAN (RJ45), IR IN, USB, MPI, DC In, RF/AC In [PoC (Power over Coax)] 75 x 75 mm Fronte Black / Back Black 23.5mm (T/L/R) / 59.7mm (B) 15.4" x 11" x 18" / 39.1 x 278.6 x 46.1 mm 18" x 7.9" x 14" / 458.0 x 201.0 x 356.0 mm 6.4 lbs / 2.9 kg 8.0 lbs / 3.7 kg 9.9 lbs / 4.5 kg Input: 100V - 240V AC 50/60Hz, Output: 19V DC 3.42A
JACK INTERFACE	Set Rear VESA Color Bezel Width W x H x D (without packing or arm adaptor) W x H x D (with packing, without arm adaptor) Weight (without packing or arm adaptor) Weight (without packing, with arm adaptor) Weight (including packing and arm adaptor) Optional Adapter (AM-PW18BA) Max PoC (Power over Coax)	Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module) HDMI/HDCP In, LAN (R145), IR IN, USB, MPI, DC In, RF/AC In [PoC (Power over Coax)] 75 x 75 mm Front: Black / Back: Black 23.5mm (Tr/MR/ 59.7mm (B)) 15.4" x 11" x 18" / 391.4 x 278.6 x 46.1 mm 18" x 7.9" x 14" / 458.0 x 201.0 x 356.0 mm 6.4 lbs / 2.9 kg 8.0 lbs / 3.7 kg 9.9 lbs / 4.5 kg Input: 100V - 240V AC 50/60Hz, Output: 19V DC 3.42A 35W Range 20V - 34V AC or DC
JACK INTERFACE MECHANICAL	Set Rear VESA Color Bezel Width W x H x D (without packing or arm adaptor) W x H x D (with packing, without arm adaptor) Weight (without packing or arm adaptor) Weight (without packing or arm adaptor) Weight (without packing, with arm adaptor) Weight (including packing and arm adaptor) Optional Adapter (AM-PW18BA) Max PoC (Power over Coax) Standby	Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module) HDMI/HDCP In, LAN (R:45), IR IN, USB, MPI, DC In, RF/AC In [PoC (Power over Coax)] 75 x 75 mm Front: Black / Back: Black 23.5mm (TI/LR) / 59.7mm (B) 15.4" x 11" x 1.8" / 391 4 x 278.6 x 46.1 mm 18" x 7.9" x 14" / 458.0 x 201.0 x 356.0 mm 6.4 lbs / 2.9 kg 8.0 lbs / 3.7 kg 9.9 lbs / 4.5 kg Input: 100V - 240V AC 50/60Hz, Output: 19V DC 3.42A 35W Range 20V - 34V AC or DC Adapter 0.5W \(\) / PoC: 0.5W \(\)
JACK INTERFACE MECHANICAL	Set Rear VESA Color Bezel Width W x H x D (without packing or arm adaptor) W x H x D (with packing, without arm adaptor) Weight (without packing or arm adaptor) Weight (without packing, with arm adaptor) Weight (including packing and arm adaptor) Optional Adapter (AM-PW18BA) Max PoC (Power over Coax)	Energy Saving, Motion Eye Care, USB Cloning Headphone Out (replaceable module) HDMI/HDCP In, LAN (R145), IR IN, USB, MPI, DC In, RF/AC In [PoC (Power over Coax)] 75 x 75 mm Front: Black / Back: Black 23.5mm (Tr/MR/ 59.7mm (B)) 15.4" x 11" x 18" / 391.4 x 278.6 x 46.1 mm 18" x 7.9" x 14" / 458.0 x 201.0 x 356.0 mm 6.4 lbs / 2.9 kg 8.0 lbs / 3.7 kg 9.9 lbs / 4.5 kg Input: 100V - 240V AC 50/60Hz, Output: 19V DC 3.42A 35W Range 20V - 34V AC or DC

 $Copyright\ 2022\ ^{\circ}\!LG\ Electronics\ USA, Inc.,\ 2000\ Millbrook\ Drive\ Lincolnshire,\ IL\ 60069,\ USA.$

All rights reserved. LG and the LG logo are registered trademarks of LG Corp. All other products and brand names are trademarks or registered trademarks of their respective companies.

Designs, features, and specifications are subject to change without notice. All screen images are simulated. $SPEC_15LS766F_072232_LR$

